

Energy Management for Large Society by Using Renewable Energy Sources

Prof. Kanawade M. T.¹, Mr. Adep Swapnil², Mr. Autade Abhijit³,

Miss. Chavhan Anisha⁴, Miss. Sanap Sushma⁵

Professor, Department of Electronics Engineering¹

Students, Department of Electronics Engineering^{2,3,4,5}

Amrutvahini College of Engineering, Sangamner, Maharashtra, India

Abstract: For very long-time power outage, power interrupt and also unexpected routine of power line maintenance is of the major problem faced in industries, hospitals, office and residential areas whole over the world. For that case, this project provides an automatic operation of electrical power distribution system; the rapid and reliable transfer of the system from one power source to another during specific event such as power outage, power interrupt, routine power line maintenance to achieve the reliability of such system. And also, sudden fluctuation in voltage is very big and serious problem in industries and home appliances and it causes losses in electrical circuits. These losses cause low power factor in the supply and by much amount of power is going to be wasted. These fluctuations may significantly impact the power quality as well as the reliability of other voltage controlling devices. Therefore, due to this fluctuation; much costly & precious equipment may get damaged. To avoid all over problems we design system for under over voltage protection, auto power switch between mains and solar power inverter. Here we are using different sensors like voltage sensor, current sensor, PIR and LDR sensor, fire sensor to give input to microcontroller. In this project we will use PIC 18f4520 microcontroller. All parameter will display on LCD display. To control switching between power sources as well as light, sprinkler, load we will use different relays

Keywords: Renewable Energy, Microcontroller, 3-Phase Sensing, Solar supply

REFERENCES

- [1]. Hawkes, A., & Leach, M. (2007). Cost-effective operating strategy for residential microcombined heat and power. *Energy*, 32(5), 711-723.
- [2]. Heshmati A. (2014), "Demand, Customer Base-Line and Demand Response in the Electricity Market: A Survey", *Journal of Economics Surveys* 28(3).
- [3]. Huo, M., Zhang, X., & He, J. (2011). Causality relationship between the photovoltaic market and its manufacturing in China, Germany, the US, and Japan. *Frontiers in Energy*, 5(1), 43-48.
- [4]. IEA. (2012a). *Energy Technology Perspectives 2012*: OECD Publishing. IEA.
- [5]. (2012b). *Medium-Term Renewable Energy Market Report 2012*: OECD Publishing. IEA.
- [6]. (2012c). *World Energy Outlook 2012*: OECD Publishing.
- [7]. Ito, M., Kato, K., Komoto, K., Kichimi, T., & Kurokawa, K. (2008). A comparative study on cost and life-cycle analysis for 100 MW very large-scale PV (VLS-PV) systems in deserts using m-Si, a-Si, CdTe, and CIS modules. *Progress in Photovoltaics: Research and Applications*, 16(1), 17-30.
- [8]. Jacobsson, S., & Bergek, A. (2004). Transforming the energy sector: the evolution of technological systems in renewable energy technology. *Industrial and corporate change*, 13(5), 815-849.
- [9]. Jäger-Waldau, A. (2006). European Photovoltaics in world wide comparison. *Journal of noncrystalline solids*, 352(9), 1922-1927.
- [10]. Jansen, B., Binding, C., Sundstrom, O., & Gantenbein, D. (2010). Architecture and communication of an electric vehicle virtual power plant. Paper presented at the Smart Grid Communications (SmartGridComm), 2010 First IEEE International Conference on.

- [11]. Kaldellis, J., Kapsali, M., & Kavadias, K. (2010). Energy balance analysis of wind-based pumped hydro storage systems in remote island electrical networks. *Applied energy*, 87(8), 2427-2437