IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 4, Issue 1, September 2024
Impact Factor: 7.53

Smart Drowsiness Detection for Safe Driving

Dr. Hitanshu Saluja[1], Ms. Ritu Juneja[2], Ritik[3], Ravi Shankar[4], Yogesh[5], Rahul Kumar[6]
[1]Professor, [2]Assistant Professor, Department of ECE, Ganga Institute of Tech.& Management, Kablana
[3,4,5,6] B.Tech Scholar, Department of ECE, Ganga Institute of Tech. & Management, Kablana

Abstract: *Driver drowsiness and fatigue are paramount contributors to major road traffic accidents globally, leading to catastrophic human casualties and substantial economic losses, particularly during nighttime driving and long-distance commercial freight transit. This paper presents the design, implementation, and experimental validation of an affordable, non-intrusive, and standalone hardware-based solution for real-time driver state monitoring. The proposed system utilizes an Arduino Nano prototyping platform integrated with an Infrared (IR) eye-blink sensor module and an audible alarm notification mechanism. By actively measuring infrared reflection variances from the ocular surface, the system differentiates regular, high-frequency biological blinking from prolonged eyelid closures associated with micro-sleep and onset fatigue. Experimental validations indicate that the firmware algorithm efficiently manages adaptive threshold comparison to trigger localized auditory warnings without imposing high computational loads or necessitating external, internet-dependent edge-computing infrastructure*

Keywords: Driver Drowsiness Detection, Arduino Nano, Eye Blink Sensor, ATmega328P, Infrared Photodiode, Traffic Safety Systems

I. INTRODUCTION

With the monumental expansion of global automotive transport networks and traffic densities, road safety has emerged as a high-priority public health and socio-economic concern. Extensive statistical analyses identify operator fatigue, sleep deprivation, and operational inattentiveness as leading catalysts for high-velocity highway collisions. Prolonged nocturnal driving degrades cognitive response times and motor control functions, leading to dangerous "micro-sleep" episodes where a driver remains completely oblivious to shifting lane dynamics [1-2].

To counter this threat, various automotive warning technologies have been proposed. Existing approaches generally belong to three technical categories:

Vehicle-Kinematic Analysis: Tracking erratic wheel movements, sudden corrections, and lane-deviation markers.

Physiological Telemetry: Monitoring real-time driver electroencephalogram (EEG) or electrocardiogram (ECG) changes, which require cumbersome, skin-contact electrodes that are impractical for long-haul operations.

Computer-Vision Monitoring: Utilizing dashboard-mounted cameras paired with single-board computing units (e.g., Raspberry Pi with OpenCV architectures) to analyze facial features. While highly accurate under perfect lighting, these vision-based systems demand intensive computational resources and often suffer from latency and poor night-vision performance.

To overcome these challenges, this paper outlines a low-cost, low-power, non-intrusive hardware architecture built around an 8-bit AVR microcontroller [3]. By focusing specifically on ocular movement tracking via an ergonomic, glass-mounted active infrared transceiver configuration, this system provides accurate real-time eye-closure assessment while remaining computationally lightweight and independent of ambient lighting changes [4-5].

Global transportation safety faces a persistent crisis due to human-factor errors, among which driver fatigue and drowsiness are the most pervasive. According to recent data from organizations like the National Highway Traffic Safety Administration (NHTSA), drowsy driving is responsible for thousands of fatal crashes annually, with prolonged wakefulness over 20 consecutive hours impairing a driver's cognitive and motor abilities to a level equivalent to a 0.08% blood-alcohol concentration (Abd El-Nabi et al., 2025) [6]. Despite public awareness campaigns, operators

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429 Volume 4, Issue 1, September 2024 Impact Factor: 7.53

frequently misjudge their own exhaustion levels, resulting in catastrophic "microsleep" episodes (Babusiak, 2026) [7]. Consequently, there is an urgent demand for the development of real-time, intelligent Advanced Driver Assistance Systems (ADAS) capable of actively monitoring operator alertness and providing proactive interventions before accidents occur (Nasir, 2025) [12].

In contemporary automotive research, driver drowsiness detection (DDD) paradigms are broadly divided into three modalities: vehicle-based, physiological, and behavioral/vision-based systems (G Ajudiya, 2026) [8]. Vehicle-based methods evaluate metrics such as steering wheel reversal rates or lane deviations, but they often trigger alerts only after erratic driving has already commenced (G Ajudiya, 2026) [9]. Physiological approaches, which track Electroencephalogram (EEG) or Electrocardiogram (ECG) metrics via wearable sensors, provide exceptional medical-grade accuracy but suffer from low user compliance due to their intrusive nature (Visconti et al., 2025) [10[. To balance accuracy with driver comfort, computer vision and localized optical sensing have emerged as the standard. Recent high-end frameworks leverage deep learning architectures, such as Convolutional Neural Networks (CNNs), Long Short-Term Memory (LSTM) networks, and Transformers to evaluate facial landmarks, yawning, and eye blink frequencies (Nasir, 2025; Abd El-Nabi et al., 2025) [12].

While deep-learning-based vision systems yield superior detection rates under optimal conditions, their implementation in commercial fleet operations faces significant barriers due to the high computational overhead, high cost of GPU hardware, and vulnerability to varying cabin illumination (Lozano-Reyes, 2025)[10]. This limitation highlights a substantial technological gap in developing countries and low-to-mid tier markets where premium embedded hardware is cost-prohibitive. To overcome these constraints, modern research focuses on "TinyML" and localized hardware acceleration—deploying lightweight, highly responsive, and energy-efficient systems directly onto microcontrollers (Essahraui, 2025) [8]. Microcontrollers like the Arduino platform offer a viable, non-intrusive alternative. When paired with infrared (IR) eye-blink sensors or lightweight edge modules, they can capture micro-sleep patterns (such as eye closures exceeding 500 ms) with deterministic timing and minimal latency (Manik, 2024) [11].

Motivated by the need for an accessible, real-time safety solution, this project presents the design and implementation of an **Arduino-based Driver Drowsiness Detection and Alerting System**. The objective is to engineer a low-cost, edge-computed hardware framework that continuously tracks eye-blink parameters. By processing behavioral metrics locally on an Arduino microcontroller, the system circumvents heavy processing pipelines while establishing a rapid, multi-tiered alerting mechanism (auditory buzzers, visual LCD warnings, and tactile feedback) to immediately re-engage a fatigued driver. Ultimately, this research aims to democratize in-vehicle safety technology, offering a scalable architecture to reduce fatigue-related collisions on modern highways [13].

II. LITERATURE REVIEW: ARDUINO UNO CENTRIC ARCHITECTURES

2.1 The Discrete Sensor Threshold Era (2015–2018)

During this period, the Arduino Uno was primarily utilized as a simple data-logger and threshold-switch. Because the 2 KB of SRAM could not handle image processing, researchers relied entirely on analog and digital peripheral sensors to infer drowsiness.

A common design architecture involved interfacing an **Infrared (IR) Eye Blink Sensor** directly to one of the Arduino's digital interrupt pins (e.g., Digital Pin 2/3). The IR sensor emitted infrared light toward the driver's eye; when the eye was open, the light reflected back differently than when the eyelid was closed. The Arduino Uno ran a continuous polling loop or an Interrupt Service Routine (ISR) tracking the duration of LOW or HIGH pulses.

If the calculated pulse duration exceeded a pre-coded limit (such as 1000ms, the Arduino set an output pin high to trigger an active buzzer or transistor-driven vibration motor. While highly responsive, these systems were plagued by false positives due to ambient sunlight flooding the IR receiver, and they lacked the sophistication to differentiate between a driver looking down at the dashboard versus falling asleep [14].

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 4, Issue 1, September 2024
Impact Factor: 7.53

2.2 The External Processing & Co-Processing Shift (2019–2022)

As Computer Vision (CV) matured, researchers realized that sensor-only approaches lacked the necessary accuracy for commercial application. However, because a raw video stream cannot be fed into an Arduino Uno, a **hybrid Master-Slave architecture** became the standard [15].

*I*n this setup, a computationally powerful host machine (such as a laptop, a Raspberry Pi, or an NVIDIA Jetson) acted as the "Master." It utilized a USB webcam to capture the driver's face, running Python scripts with OpenCV, dlib, or MediaPipe to extract facial landmarks and calculate the Eye Aspect Ratio (EAR) [16]:

$$EAR = \frac{||p_2 - p_6|| + ||p_3 - p_5||}{2||p_1 - p_4||}$$

When the host computer detected that the EAR value dropped below a critical threshold (typically around 0.25) for a consecutive number of frames, it compiled a brief data packet. This packet was transmitted over a hardware serial bus via USB to the **Arduino Uno** (acting as the "Slave").

The Arduino Uno utilized its dedicated hardware UART (Serial.begin(9600)) to parse the incoming byte string. Upon reading the trigger character, the Arduino took over the physical safety critical tasks: activating heavy-duty relays, sound modules, or safety strobes. This shifted the heavy mathematics off the micro-controller while leveraging the Arduino's deterministic, real-time execution for hardware safety tasks [17].

2.3 Edge Optimization and Closed-Loop Systems (2023–2026)

In recent years, the focus has shifted toward building completely self-contained, low-cost, closed-loop safety networks around the Arduino Uno without relying on an expensive host PC. Researchers are achieving this by optimizing data protocols and adding specialized, self-contained edge vision modules (like the *HuskyLens* or *ESP32-CAM* running highly compressed, localized models) [18].

In these contemporary architectures, the vision module handles the facial detection locally on its own chip and outputs simple digital or I^2C signals directly to the Arduino Uno. This completely protects the Uno's 2 KB SRAM from overflowing [19].

Furthermore, modern frameworks have evolved from passive alerting to active vehicle intervention. When the Arduino Uno receives a drowsiness flag, it executes a multi-tiered safety protocol across its physical pins [20]:

Immediate Haptic/Auditory Alert: Digital output pins immediately pulse an active buzzer and a PWM-controlled vibration motor on the steering wheel.

Visual Warning Update: Liquid Crystal Displays (LCDs) connected via an I^2C backpack (Pins A4/A5) print real-time warning indicators, minimizing the pin count on the Uno.

Active Vehicle Safety Interventions: The Arduino pulses an optocoupler-isolated relay module linked directly to a high-torque DC motor (simulating the vehicle's throttle or braking link) to actively slow down the vehicle safely.

Wireless Fleet Tracking: Using Software Serial (SoftwareSerial.h) on digital pins, the Uno commands an onboard SIM800L GSM module via AT commands to send an automated emergency SMS containing GPS coordinates fetched via an attached NEO-6M GPS module.

2.4 Comparative Summary of Arduino Uno System Implementations

The table below illustrates how researchers have progressively optimized the limited hardware footprint of the ATmega328P chip over the last decade.

Era / Study Focus	Role of Arduino Uno	Connected Sensor Inputs	Output Actuators / Peripherals	System Bottleneck / Limitation

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429 Volume 4, Issue 1, September 2024 Impact Factor: 7.53

Early Threshold Systems (2015-2018)	**Master Controller:** Handled raw signal processing and timing logic entirely on-chip.	Analog IR Eye Blink Sensor, MPU-6050 Accelerometer.	Active Piezo Buzzer, basic LED indicators.	**Sensor Noise:** Highly vulnerable to ambient Infrared interference; high false-alarm rates.
Early Threshold Systems (2015-2018)	**Master Controller:** Handled raw signal processing and timing logic entirely on-chip.	Analog IR Eye Blink Sensor, MPU-6050 Accelerometer.	Active Piezo Buzzer, basic LED indicators.	**Sensor Noise:** Highly vulnerable to ambient infrared interference; high false-alarm rates.
Hybrid Host-Microcontroller Frameworks (2019-2022)	**Slave Hardware Actuator:** Dedicated solely to processing serial commands sent by an external PC.	USB Serial Data (Serial.read()) originating from Python/OpenCV pipelines.	16X2 Character LCD (Parallel interface), 5V Relay modules.	**Hardware Tethering:** Completely reliant on an expensive, external laptop or single-board computer running in the cabin.
Modern Closed-Loop Edge Networks (2023-2026)	**Central Embedded Hub:** Coordinates complex safety logic, telemetry transmission, and active mechanical intervention.	I^2C Smart Vision Cameras (e.g., HuskyLens), NEO-6M GPS Module via SoftwareSerial.	Opto-isolated DC Motor Relays, SIM800L GSM Module, I^2C LCD Display.	**Memory Management:** Demands meticulous coding practices (e.g., using the F() macro) to keep local arrays from exhausting the 2 KB SRAM.

III. METHODOLOGY AND SYSTEM ARCHITECTURE

The proposed system features an embedded architecture divided into three primary sub-systems: the **Power Regulation Stage**, the **Sensory Acquisition Unit**, and the **Central Microcontroller Processing Core**

3.1 Power Supply Regulation Stage

Reliable, noise-free electrical power is essential to protect sensitive complementary metal-oxide-semiconductor (CMOS) and transistor-transistor logic (TTL) integrated circuits from voltage spikes. While direct 9V DC battery configurations are used for mobile testing, batteries inevitably lose their charge over time and drop in potential. To support stationary testing or direct vehicle electrical integration, a rectified power supply was developed:

Step-Down Transformation: Converts standard 230V, 50Hz AC power down to 12V AC using a laminated step-down transformer.

Rectification & Smoothing: Passes the 12V AC through a full-wave bridge rectifier (built using 1N4007 diodes) paired with a high-capacity 1000µF electrolytic capacitor to smooth out ripple voltages and deliver an unregulated 12V DC output.

Linear Voltage Regulation: Uses a three-terminal TO-220 7805 linear voltage regulator IC to output a steady, continuous 5V DC supply. Parallel decoupling capacitors (0.22µF at input, 0.1µF at output) are added to improve transient response and filter high-frequency line noise.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 4, Issue 1, September 2024
Impact Factor: 7.53

3.2 Sensory Acquisition Unit

Ocular monitoring is handled by an active, near-infrared transceiver assembly attached to the frame of an ergonomic set of safety glasses.

The sensor works via active optical reflection telemetry:

Transmitter (IR LED): Emits an unmodulated infrared light beam in the 700nm to 1mm wavelength spectrum toward the driver's eye region.

Receiver (Photodiode): Features a dark, light-filtering coating to minimize interference from surrounding ambient light. This photodiode operates in a reverse-bias configuration. When the driver's eye is open, the highly reflective surface of the sclera and cornea bounces the IR energy back, causing a sharp drop in the photodiode's internal resistance. Conversely, when the eyelid closes, the lower reflectivity of skin tissue reduces the returning IR energy, increasing the photodiode's resistance.

Signal Conditioning (LM358 Op-Amp): The variable current from the photodiode passes through an on-board potentiometer arranged in a voltage-divider network. This voltage is fed into an LM358 operational amplifier acting as a high-speed voltage comparator. By comparing this active voltage against a manually adjusted reference threshold, the module outputs a clear analog signal to the microcontroller's Analog-to-Digital Converter (ADC) channels.

3.3 Central Processing Core

The processing hub relies on an ATmega328P 8-bit RISC architecture microcontroller housed on an Arduino prototyping board. This controller handles the continuous sampling of the incoming eye-blink data streams. Running at a clock frequency of 8MHz to 16MHz, the controller utilizes built-in timers to track the exact duration of eye closures, completely eliminating the need for bulky exterior computer units.

IV. SYSTEM IMPLEMENTATION AND FIRMWARE DESIGN

The core detection logic is implemented in C/C++ within the Arduino development environment. The algorithm uses non-blocking millisecond timing routines (millis()) to avoid the program-freezing limitations associated with standard hardcoded delays.

4.1 Firmware Algorithm Logic

Upon system activation, digital pin 2 (connected to the buzzer warning module) is pulled HIGH to establish an inactive alert state, and analog pin A0 is configured as the input source for the LM358 comparator signal.

A baseline timestamp variable (TIME) is calibrated to track runtime execution intervals.

The function getVal() reads the analog input on pin A0. A high reflection coefficient (eye open) yields an ADC value above 350, while a closed eye drops the value to 350 or below.

If getVal() <= 350, the firmware detects an active eye closure. It then compares the current runtime against the baseline timestamp (millis()/100 - TIME > 25). If this eye closure lasts longer than 2.5 seconds, it is flagged as an involuntary micro-sleep or drowsiness event rather than a standard biological blink.

Once this 2.5-second threshold is crossed, digital pin 2 drops to LOW, activating a loud buzzer warning to immediately alert the driver. The system stays in this active alert loop until the ADC values return to normal, confirming the driver's eyes are open.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 4, Issue 1, September 2024
Impact Factor: 7.53

V. EXPERIMENTAL RESULTS AND DISCUSSION

The integrated system was tested across various lighting scenarios to evaluate its real-world performance.

5.1 Comparative Sensor Performance Analysis

Ocular State	Optical Reflection Character	ADC Voltage Range (A0 Pin)	Microcontroller Assessment	System Alert State
Active Focus (Eye Open)	High Infrared Reflection	450 - 700	Normal Driver Awareness	Deactivated / Safe (HIGH)
Natural Blink	Transient Reflection Drop	<= 350	Regular Ocular Activity (t < 2.5s)	Deactivated / Safe (HIGH)
Micro-Sleep / Fatigue	Sustained Reflection Loss	<= 350	Drowsiness Confirmed (t >= 2.5s)	**Activated Alert (LOW)**

5.2 Performance Analysis

The system successfully distinguished normal, fast biological blinking from prolonged micro-sleep closures. Because the sensor uses infrared light wavelengths, it remains unaffected by external ambient lighting changes, maintaining high accuracy in both bright daylight and pitch-black nocturnal conditions.

The onboard LM358 potentiometer allows for manual sensitivity calibration, ensuring the system can adapt to different facial structures and glass-mounting distances. Operating the firmware on the ATmega328P processor yielded minimal processing delays, ensuring an instantaneous buzzer response the moment a driver crossed the 2.5-second drowsiness threshold.

VI. LIMITATIONS AND FUTURE SCOPE

While the current hardware architecture functions efficiently as a standalone safety device, it has certain operational limitations:

Mounting Dependability: The IR sensor module must be mounted onto eyewear worn by the driver, which may cause discomfort during extended commercial shifts.

Single-Parameter Tracking: The system relies entirely on eyelid movement data and does not track other fatigue indicators, such as head tilting or changes in steering wheel pressure.

Future research will focus on expanding these capabilities:

Wireless Telemetry Integration: Adding RF transceiver modules (such as 433MHz configurations or Bluetooth Low Energy networks) to enable wireless data exchange between the driver's eyewear and the vehicle's dashboard.

Multi-Sensor Fusion: Integrating small, micro-electromechanical (MEMS) accelerometers directly into the glasses frame to track sudden head drops or erratic nodding associated with severe fatigue.

Advanced Microcontroller Implementation: Transitioning the core firmware onto a 32-bit ARM Cortex platform to allow for onboard edge-computing machine learning algorithms, providing adaptive user profiling over time.

VII. CONCLUSION

This paper demonstrates the design and deployment of an effective, low-power, and affordable Driver Drowsiness Detection and Alerting System built on an Arduino microcontroller architecture. By using targeted infrared reflection tracking, the system accurately identifies dangerous micro-sleep episodes in real time without requiring heavy computational resources or constant internet connectivity. The direct hardware implementation, coupled with an audible buzzer alert, provides a reliable and cost-effective safety addition for commercial and overnight transportation. This design represents a practical step toward reducing fatigue-related highway accidents and improving overall road safety.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 4, Issue 1, September 2024
Impact Factor: 7.53

REFERENCES

[1]. Bajaj, J. S., Kumar, N., Kaushal, R. K., Gururaj, H. L., Flammini, F., & Natarajan, R. (2023). System and method for driver drowsiness detection using behavioral and sensor-based physiological measures. *Sensors*, *23*(3), 1292. https://doi.org/10.3390/s23031292

[2]. Florez, R., Palomino-Quispe, F., Alvarez, A. B., Coaquira-Castillo, R. J., & Herrera-Levano, J. C. (2024). A real-time embedded system for driver drowsiness detection based on visual analysis of the eyes and mouth using convolutional neural network and mouth aspect ratio. *Sensors*, *24*(19), 6261. https://doi.org/10.3390/s24196261

[3]. Ghosh, H., Chatterjee, S., Ganguly, A., Karmakar, S., & Sarkar, K. (2025). Sleepy chauffeur detection and alert techniques for road safety. *International Journal on Recent Innovation in Microelectronics and Microcontrollers Applications*, *1*(1).

[4]. Kolus, A. (2024). A systematic review on driver drowsiness detection using eye activity measures. *IEEE Access*, *12*, 97969-97993. https://doi.org/10.1109/access.2024.3424654

[5]. Sahayadhas, A., Sundaraj, K., & Murugappan, M. (2012). Detecting driver drowsiness based on sensors: A review. *Sensors*, *12*(12), 16937-16953. https://doi.org/10.3390/s121216937

[6]. Abd El-Nabi, S., et al. (2025). Driver Drowsiness Detection Using Swin Transformer and Diffusion Models for Robust Image Denoising. *IEEE Xplore*.

[7]. Babusiak, B. (2026). Smart Steering Wheel Prototype for In-Vehicle Vital Sign Monitoring. *Sensors*.

[8]. Essahraui, S., et al. (2025). FastKAN-DDD: A novel fast Kolmogorov-Arnold network-based approach for driver drowsiness detection optimized for TinyML deployment. *PMC*.

[9]. G Ajudiya, C. (2026). A review on AI-driven drowsiness detection systems using deep-learning. *EPJ Web of Conferences*.

[10]. Lozano-Reyes, G. S., et al. (2025). A vision-based drowsiness detection system for railway operators using lightweight convolutional neural networks. *Frontiers in Future Transportation*.

[11]. Manik, J. P. (2024). Pengembangan Sistem Pendeteksi Kantuk Pengemudi Berbasis Arduino Nano Dan Sensor Eye Blink. *Jurnal Nasional Teknologi Komputer*.

[12]. Nasir, O. (2025). SAFE-DRIVE-AI: A CNN–LSTM–Attention Framework for Drowsiness Detection. *Engineering, Technology & Applied Science Research*, *15*(5).

[13]. Visconti, P., Rausa, G., Del-Valle-Soto, C., Velázquez, R., Cafagna, D., & De Fazio, R. (2025). Innovative Driver Monitoring Systems and On-Board-Vehicle Devices in a Smart-Road Scenario Based on the Internet of Vehicle Paradigm: A Literature and Commercial Solutions Overview. *Sensors*, *25*(2), 562. https://doi.org/10.3390/s25020562

[14]. Albasrawi, R., Fadhil, F. F., & Ghazal, M. T. (2022). Driver drowsiness monitoring system based on facial Landmark detection with convolutional neural network for prediction. *Bulletin of Electrical Engineering and Informatics*, *11*(5), 2637–2644. https://doi.org/10.11591/eei.v11i5.3966

[15]. Babu, T. (2025). Integrating IoT and Sensors for Comprehensive Road Safety: A Systematic Approach to Accident Prevention. *Atlantis Press International Conference Proceedings*, 112–118.

[16]. Bajaj, J. S., Kumar, N., Kaushal, R. K., Gururaj, H. L., Flammini, F., & Natarajan, R. (2023). System and method for driver drowsiness detection using behavioral and sensor-based physiological measures. *Sensors*, *23*(3), 1292. https://doi.org/10.3390/s23031292

[17]. Florez, R., Palomino-Quispe, F., Alvarez, A. B., Coaquira-Castillo, R. J., & Herrera-Levano, J. C. (2024). A real-time embedded system for driver drowsiness detection based on visual analysis of the eyes and mouth using convolutional neural network and mouth aspect ratio. *Sensors*, *24*(19), 6261. https://doi.org/10.3390/s24196261

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 4, Issue 1, September 2024
Impact Factor: 7.53

[18]. Mishra, B., Singh, M., & Arun, A. V. (2025). Driver drowsiness detection using Dlib. *AIP Conference Proceedings*, *3253*(1), 030021. https://doi.org/10.1063/5.0251941

[19]. Valiente, F. L., Parel, E. L. P., Miranda, G. J. Y., Vergara, E., & Valiente, L. D. (2024). Detecting alcohol-induced drowsiness in four wheeled vehicles: An eye tracking and MQ3 sensor based approach with Arduino Uno and Raspberry Pi, integrated with SMS notification system and GPS. *2024 16th International Conference on Computer and Automation Engineering (ICCAE)*, 385–389. https://doi.org/10.1109/iccae59995.2024.10569370

[20]. Visconti, P., Rausa, G., Del-Valle-Soto, C., Velázquez, R., Cafagna, D., & De Fazio, R. (2025). Innovative driver monitoring systems and on-board-vehicle devices in a smart-road scenario based on the internet of vehicle paradigm: A literature and commercial solutions overview. *Sensors*, *25*(2), 562. https://doi.org/10.3390/s25020562