

International Journal of Advanced Research in Science, Communication and Technology

International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal

Volume 5, Issue 10, May 2025



# **Enemy Tank Detection**

Mr. Omprakash Wagh, Ms. Pallavi Shinde, Mr. Swapnil Gawale, Ms. Chetana Khairnar

Student, Department of Electronics and Telecommunication Asst. Prof., Department of Electronics and Telecommunication NBN Sinhgad Technical Institute Campus, Pune, India

**Abstract**: This paper presents the design and implementation of an Automated Enemy Tank Detection utilizing modern technologies such as image processing, wireless communication, and the Internet of Things (IoT). The system detects and differentiates between friendly and enemy tanks using infrared (IR) identification signals and automatically adjusts a servo motor for accurate targeting. It also features real-time monitoring and data transmission capabilities to provide continuous situational awareness to military personnel, enhancing threat response efficiency. Additionally, the system can intercept radio frequency (RF) signals to expand its surveillance capabilities. The proposed framework reduces human intervention, accelerates response times, and ensures adaptability for future advancements like artificial intelligence (AI) integration for autonomous defence operations.

**Keywords**: Enemy tank detection, Border security, Image processing, Raspberry Pi, Servo motor, IR, IoT, ATmega328, Auto- mated defence system

# I. INTRODUCTION

Time of rising geopolitical tensions and swift military technology breakthroughs. Finding and identifying enemy tanks is a crucial topic of attention in this arena since they represent serious risks to the safety and security of the country. Even while they can be somewhat effective, traditional monitoring techniques frequently rely mostly on human participation, which can cause delays and perhaps inaccurate danger assessments. Due to this constraint, an automated, dependable system that can swiftly identify and react to enemy tanks must be developed in order to improve operational effectiveness.

The system determines a tank's location in degrees when it detects one, enabling precise firing mechanism changes. A servo motor makes this change possible by adjusting the firing mechanism's angle in reaction to the location of the tank, which maximizes response precision. The system uses an IR transmitter to transmit identification signals in order to discriminate between friendly and enemy tanks. The system is designed to fire if the detected tank is proven to be an enemy; on the other hand, if the tank is determined to be friendly, no action is performed, so averting friendly fire, an all too common risk in military operations.

The system may adjust and enhance its recognition abilities over time by learning from previous experiences and improving its operational procedures thanks to the inclusion of image processing technologies like contour detection and machine learning additionally, the "Enemy Tank Detection" system is part of the proactive border management approach in addition to being a defensive instrument. Military 1 forces can remain attentive by using this automated detection technique to quickly identify possible threats before they develop into more significant battles. This capacity has the potential to greatly improve border region security, preventing hostile acts and giving military troops and civilian's peace of mind. The expansion of sophisticated military hardware in recent years has highlighted the need for detection and response systems that are equally sophisticated. Conventional surveillance methods necessitate technological augmentation since they are frequently constrained by human capabilities and external circumstances. In order to overcome these drawbacks, the suggested system offers an automated approach that can also adjust to different environmental circumstances. The effectiveness of detecting systems can be significantly impacted by variables like weather, topography, and time of day. For this reason, it is crucial to incorporate robust image processing techniques.

Copyright to IJARSCT www.ijarsct.co.in







International Journal of Advanced Research in Science, Communication and Technology

International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal

#### Volume 5, Issue 10, May 2025



# **II. LITERATURE SURVEY**

Ahmed and colleagues, in their 2021 publication in the IEEE Internet of Things Journal, focused on the integration of IoT technologies in defence for real-time monitoring and data transmission. Their research highlights how IoT systems can transmit real-time data from defence detection systems to remote servers, enabling better monitoring and quicker decision-making. The application of IoT in automated tank detection systems allows for enhanced situational awareness and immediate action based on live data, ensuring better oversight and control of the system. [1]

Garcia and Patel, in a 2020 article from the Journal of Robotics and Automation, investigated the role of servo motors in enhancing the precision of targeting systems. The study discusses how servo motors enable precise control over the position and movement of firing mechanisms, making them ideal for dynamic defence systems. This technology is critical for adjusting the firing angle accurately in real-time, which is essential for engaging moving targets such as enemy tanks in an automated defence environment. [2]

Johnson and Lee, in their 2019 paper from the International Journal of Infrared and Millimetre Waves, examined the use of infrared communication for identifying friendly and enemy units. This research highlights how modulated infrared signals can be used to classify vehicles, helping to prevent friendly fire. The system differentiates between friendly and hostile units, ensuring safe and reliable operation in automated defence systems. The use of IR communication aligns with the objective of identifying enemy tanks while avoiding harm to friendly forces. [3]

In a 2018 study published in the IEEE Transactions on Neural Networks and Learning Systems, Smith and colleagues explored the use of the YOLO (You Only Look Once) algorithm for real-time object detection. The paper showcases YOLO's ability to quickly and efficiently detect multiple objects in a single image pass, making it ideal for applications requiring rapid detection, such as military vehicle recognition. YOLO's speed and accuracy in real-time scenarios provide significant improvements in automated detection systems, which is highly relevant for enemy tank identification in border security. [4]

### **III. METHODOLOGY**

The "Enemy Tank Detection" project aims to provide a robust solution to enhance border security through the use of advanced image processing, real-time data transmission, and machine automation. As geopolitical landscapes shift and technological advancements become increasingly integrated into military operations, security systems must adapt accordingly. This project focuses on addressing one of the most critical aspects of border security the detection, identification, and elimination of enemy vehicles, particularly tanks, in real- time, using automated systems to minimize human intervention and error.

# A. Overview of the project

The "Enemy Tank Detection" has demonstrated promising results in its ability to detect and respond to potential threats in real-time. The system effectively identifies tanks through image processing with the Raspberry Pi 4, achieving high accuracy in distinguishing tanks from other objects in the environment. During testing, the servo motor adjusted the firing mechanism with precision, based on the calculated position of detected tanks, which resulted in accurate targeting. The IR-based identification reliably distinguished between friendly and enemy units, ensuring that friendly fire incidents were prevented. This aspect of the system is critical for deployment in mixed operational environments, where maintaining accuracy is essential for safety. Data transmission to an IoT server was successful, enabling real-time monitoring and analysis of detected threats. The latency between detection and data reporting remained minimal, making the system effective for real-time applications.

# **B.** Flow chart

System Initialization: The system is started, initializing all the hardware and software components.

Image Capture: The Raspberry Pi captures an image through the connected camera.

Tank Detection (Image Processing): The system processes the image to detect whether there is a tank. If no tank is detected, the system continues to monitor by capturing new images. If a tank is detected, the system calculates the tank's location in degrees and adjusts the firing angle using a servo motor.

Copyright to IJARSCT www.ijarsct.co.in







International Journal of Advanced Research in Science, Communication and Technology

International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal

Volume 5, Issue 10, May 2025



IR Identification: The system sends an IR signal to the detected tank to check if it is friendly or hostile. If the tank responds (friendly), the firing mechanism is stopped. If no response is received (enemy), the system fires at the tank.



# Fig.1 flow chart

# C. Block Diagram

Transmitter Side Block Diagram

Power Supply: Provides the required voltage and current to power all components of the system, including the Raspberry Pi 4, camera, sensors, and actuators. It ensures stable operation of the hard- ware components.



#### Fig 2. Block diagram of transmitter

Raspberry Pi 4: Acts as the central processing unit (CPU) of the system, controlling all other components. It processes data from the camera for image recognition, manages the RF and IR signals, and sends commands to the servo motor, buzzer, and firing mechanism based on the detected inputs. Camera: Captures real-time images or video of the surrounding environment, which is then processed by the Raspberry Pi 4 to detect tanks or other objects of interest. It plays a crucial role in the image recognition process for identifying potential threats.

RF Receiver: Detects radio frequency signals that may indicate nearby communication activities, potentially from enemy units. It sends data to the Raspberry Pi for analysis, adding an extra layer of intelligence to detect and monitor unseen threats.

Copyright to IJARSCT www.ijarsct.co.in







International Journal of Advanced Research in Science, Communication and Technology

International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal

#### Volume 5, Issue 10, May 2025



IR Receiver: Receives infrared signals from IR transmitters on friendly units, helping to differentiate between friendly and enemy vehicles. This identification prevents the system from mistakenly targeting allied units.

IR Transmitter: Sends infrared signals to communicate with other friendly units, confirming identification to avoid friendly fire. It acts as a part of the system's safety mechanism by broadcasting signals that can be recognized by IR receivers on other friendly devices.

Servo Motor: Adjusts the angle of the firing mechanism based on the position of detected targets. Controlled by the Raspberry Pi, it ensures precise aiming of the firing gun towards the target for an accurate response.

# **Receiver Side Block Diagram**



Fig 3. Block diagram of receiver

Power supply: provides the necessary power to all components of the system, ensuring a stable voltage supply for the ATMEGA328 microcontroller, IR receiver, IR transmitter, and led indicator. It ensures that the circuit operates reliably. ATMEGA328: a microcontroller that serves as the central processing unit of the system, managing input signals from the IR receiver and controlling the outputs, including the IR transmitter and led indicator. It processes the data received and executes predefined actions, such as triggering a led or transmitting signals. IR receiver: receives infrared signals from other devices, enabling the sys- tem to detect and interpret incoming IR data. The received signals can be used to identify the presence of other units or objects, which the ATMEGA328 processes for further action.

IR transmitter: sends out infrared signals to communicate with other devices in the system. This could be used for signalling or identifying friendly units by trans- mitting a specific IR code that other systems can recognize.

Led indicator: provides a visual signal based on the input processed by the ATMEGA328. It could light up to indicate the successful reception of an IR signal, status of the system, or other alerts, offering immediate feedback to the user.

# **IV. RESULT**

The "Enemy Tank Detection" has demonstrated promising results in its ability to detect and respond to potential threats in real-time. The system effectively identifies tanks through image processing with the Rasp- berry Pi 4, achieving high accuracy in distinguishing tanks from other objects in the environment. During testing, the servo motor adjusted the firing mechanism with precision, based on the calculated position of detected tanks, which resulted in accurate targeting. The IR-based identification reliably distinguished between friendly and enemy units, ensuring that friendly fire incidents were prevented. This aspect of the system is critical for deployment in mixed operational environments, where maintaining accuracy is essential for safety. Data transmission to an IoT server was successful, enabling real-time monitoring and analysis of detected threats. The latency between detection and data reporting remained minimal, making the system to monitor communication signals that might indicate enemy activity. However, certain challenges were identified, such as occasional false positives in image detection under complex backgrounds, which could be improved with advanced machine learning algorithms. Overall, the system showed robustness and reliability across different testing scenarios, highlighting its potential for enhancing border security and automated defence operations.

Copyright to IJARSCT www.ijarsct.co.in







International Journal of Advanced Research in Science, Communication and Technology

International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal

Volume 5, Issue 10, May 2025



Fig 4. Simulation results Fig 5. Actual hardware result

# **V. CONCLUSION**

This paper presented The "Enemy Tank Detection" system has demonstrated a strong potential in enhancing automated surveillance and defense capabilities. By utilizing the Raspberry Pi 4 for image processing, the system effectively distinguishes tanks from other objects with high accuracy. The integration of a servo motor for precise targeting and an IR-based identification mechanism ensures reliable discrimination between friendly and enemy units, minimizing the risk of friendly fire. Real-time data transmission to an IoT server allows for remote monitoring and quick response, while RF detection adds another layer of intelligence by monitoring communication signals that may indicate enemy presence. The system maintained minimal latency, which is crucial for real-time threat response. These features collectively make it a promising solution for deployment in high-security zones such as border areas or sensitive military installations.

However, certain challenges were observed during testing, particularly the occurrence of false positives in complex and cluttered backgrounds. This issue can be addressed by incorporating more advanced machine learning models such as YOLO, which are designed for robust object detection under diverse environmental conditions. Additionally, enhancing the RF module range and implementing edge AI accelerators could significantly boost system efficiency. With these improvements, the system can be scaled for wider deployment, offering a cost-effective and intelligent solution for next-generation automated defense and surveillance operations.

# VI. ACKNOWLEDGMENT

This research was not funded by any grant.

We would like to express our sincere gratitude to all those who supported and guided us throughout the course of this project. First and foremost, we are thankful to our project guide, [Prof. C. H. Khairnar], for their invaluable support, technical insights, and continuous encouragement which played a crucial role in the successful completion of this work.

# REFERENCES

[1] Wiggers, K.L., Pohlod, C.D., Orlovski, R., Ferreira, R. and Santos, T.A., 2022. "Detection and counting of plants via deep learning using images col- lected by RPA". Revista Brasileira de Ci^encias Agr'arias, 17(2), p.e1353.

[2] X. Li, Y. Mao, J. Yu and Z. Mao, "Tank Armored Vehicle Target Detection Based on Improved YOLOv5s," 2024 4th International Conference on Computer Communication and Artificial Intelligence (CCAI), Xi'an, China, 2024, pp. 1-6, doi: 10.1109/CCAI61966.2024.10603112.

[3] Redmon Joseph, S. D. R. G., Farhadi, A. (2016). You only look once: Unified, real-time object detection. In Proceed- ings of the IEEE conference on computer vision and pattern recognition.

[4] W. Budiharto, V. Andreas, J. S. Suroso, A. A. S. Gunawan and E. Irwansyah, "Development of Tank- Based Military Robot and Object Tracker," 2019 4th Asia-Pacific Confer- ence on Intelligent Robot Systems (ACIRS), Nagoya, Japan,

[5] HARALICK, Robert M.; SHAPIRO, Linda G. Image seg- mentation techniques. Computer vision, graphics, and image processing, 1985, 29.1: 100-132.

Copyright to IJARSCT www.ijarsct.co.in







International Journal of Advanced Research in Science, Communication and Technology

International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal

### Volume 5, Issue 10, May 2025



[6] Amudhan, A., et al., RFSOD: a lightweight single-stage de- tector for real-time embedded applications to detect small- size objects. Journal of Real-Time Image Processing, 2021: p. 1-14.

[7] Ren, Z., Fang, F., Yan, N., & Wu, Y. (2022). "State of the art in defect detection based on machine vision", International Journal of Precision Engineering and Manufacturing-Green Technology, 9(2), 661-691.

[8] Paraskevoudis, K., Karayannis, P., & Koumoulos, E. P. (2020). "Real-time 3D printing remote defect detection (stringing) with computer vision and artificial intelligence", Processes, 8(11), 1464.

[9] R. Kabilan, R. MallikaPandeeswari, N. Lalitha, E. Kanmanikarthiga, C. Karthica and L. M. H. Sharon, "Soldier Friendly Smart And Intelligent Robot On War Field," 2022 Second International Conference on Artificial Intelligence and Smart Energy (ICAIS), Coimbatore, India, 2022, pp. 666-671, doi: 10.1109/ICAIS53314.2022.9742909.

[10] X. Li, Y. Mao, J. Yu and Z. Mao, "Tank Armored Vehicle Target Detection Based on Improved YOLOv5s," 2024 4th International Conference on Computer Communication and Artificial Intelligence (CCAI), Xi'an, China, 2024, pp. 1-6, doi: 10.1109/CCAI61966.2024.10603112.

[11] W. Budiharto, V. Andreas, J. S. Suroso, A. A. S. Gunawan and E. Irwansyah, "Development of Tank- Based Military Robot and Object Tracker," 2019 4th Asia-Pacific Conference on Intelligent Robot Systems (ACIRS), Nagoya, Japan, 2019, pp. 221-224, doi: 10.1109/ACIRS.2019.8935962



