

SmartEco Grid - Integrated System for Water and Energy Management

¹Vishwajit Santosh Mane, ²Shreyash Atul Jdhav, ³Dhiraj Prabhunath Holkunde,
⁴Sushant Sanjay Salunkhe, ⁵Ayush Santosh Pardeshi ⁶Deepak Vijaykumar Phadtre
Students, Sanjay Ghodawat Institute, Atigre¹⁻⁵
Faculty, Sanjay Ghodawat Institute, Atigre⁶

Abstract: *The Smart Eco Grid initiative aims to merge two vital intelligent systems—automated street lighting and rainwater collection for agricultural irrigation—to foster energy conservation, water preservation, and sustainable growth. The automated street lighting mechanism utilizes light-dependent resistors (LDRs) along with microcontrollers to sense surrounding light intensity, enabling the lights to activate at sunset and deactivate at sunrise. This approach reduces energy consumption, lowers electricity expenses, and ensures effective management of urban lighting without the need for manual control.*

By integrating these systems, the Smart Eco Grid not only improves urban infrastructure quality but also bolsters environmental sustainability. It decreases reliance on traditional electricity sources and groundwater, harnesses renewable resources, and contributes to the development of smart cities. This project exemplifies a model for future implementations of integrated intelligent systems that harmonize urban governance with ecological stewardship..

Keywords: Automated Street Lighting, Rainwater Collection, Intelligent Irrigation, Energy Conservation, Smart City

I. INTRODUCTION

In recent times, the rising interest in sustainable urban planning and practices has prompted the implementation of intelligent technologies aimed at conserving energy and natural resources. Automated street lighting systems are engineered to illuminate areas only when necessary, using sensors that monitor surrounding light conditions. This strategy minimizes energy use, reduces operational expenses, and improves public safety by guaranteeing that streets remain adequately lit after dark.

Similarly, rainwater harvesting has proven to be a valuable technique for water conservation, complementing conventional irrigation methods. By capturing and storing rainwater, it can be effectively used for tree care, particularly in areas where road-side greenery suffers from limited water supply.

The Smarteco Grid initiative merges these two approaches into a cohesive, integrated solution that tackles both energy and water conservation. This combined strategy not only supports environmental sustainability but also advances smart city efforts and establishes a framework for contemporary urban and rural infrastructure management. By utilizing automation and sensor-driven controls, the system guarantees efficiency, cost savings, and reliability in both lighting and irrigation systems.

To avoid double voting, the system automatically changes the database once the vote is cast.

This technique guarantees that each voter casts a single ballot, decreases election fraud, increases accuracy, and expedites vote counting. The Advanced Fingerprint Based Voting System offers a safe, effective, and dependable method of contemporary electronic voting by combining fingerprint sensors with microcontrollers and database management systems.



Objective

First, The aims of the proposed system include:

- To create an automated street lighting control system utilizing a light-dependent resistor (LDR) sensor.
- To minimize energy waste.
- To gather and store rainwater for conservation purposes.
- To utilize the collected rainwater for plant cultivation.
- To lessen the need for manual labor.
- To design an environmentally friendly and sustainable system.

II. LITERATURE REVIEW

In many regions, the current street lighting setup relies on either manual operation or timer-based controls. In manual systems, an operator is responsible for turning the lights on at dusk and off at dawn. This process is entirely reliant on human action, which can lead to situations where the operator forgets to adjust the lights at the appropriate times. Consequently, street lights may remain off when illumination is necessary, compromising road safety, or they might stay on during daylight hours, resulting in superfluous energy consumption.

Some areas have adopted timer-based systems that automate the ON and OFF times according to a predetermined schedule. However, this approach fails to account for variations in daylight due to seasons, such as longer daylight hours in summer and shorter during winter. As a result, these lights may activate prematurely or deactivate too late, further contributing to ineffective energy use. Moreover, these systems lack the capability to adjust based on real-time sunlight conditions.

Moreover, the water management systems along roadways are also lacking in efficiency. During rainfall, water typically flows along the streets and is directed toward drainage systems without being captured or preserved for future use. This practice leads to considerable waste of rainwater. Concurrently, plants and trees situated by the roadside require hydration, which is often provided through external sources like water tankers. This reliance increases overall water usage, costs, and the depletion of resources.

III. METHODOLOGY

Combined Methodology: Smart Automation for Sustainable Infrastructure.

The This study integrates automation techniques from smart street lighting and rainwater management systems using microcontrollers, sensors, and IoT technologies to enhance energy and water efficiency.

System Architecture:

A central controller (Arduino/NodeMCU) processes sensor data and controls actuators such as LEDs, pumps, and valves. LDR sensors regulate streetlight intensity, while rain, flow, and level sensors manage water collection and distribution.

Sensor-Based Operation:

LDR sensors detect ambient light for day/night operation, and IR/ultrasonic sensors detect movement to adjust lighting intensity dynamically.

Control Logic:

Rule-based automation enables streetlights to switch OFF during daytime, operate at DIM mode at night, and increase to HIGH intensity upon motion detection. The rainwater system automates water collection, storage, and distribution, with predictive optimization to prevent overflow and shortages.

IoT Integration:

IoT-enabled controllers provide real-time monitoring, remote control, and data analysis through cloud platforms, improving operational efficiency.



Site Planning and Design:

A 1 km highway stretch was selected based on solar availability, drainage, and infrastructure. Road surfaces serve as rainwater catchment areas, supported by drainage channels, filtration units, and storage tanks designed using rainfall data.

Energy Management:

A hybrid power system uses solar energy as the primary source with grid electricity as backup, ensuring uninterrupted operation.

Installation and Implementation:

The system includes installation of streetlight poles, solar panels, sensors, drainage systems, filtration units, storage tanks, and irrigation pipelines.

Performance Evaluation:

The system was assessed for lighting automation, solar efficiency, backup reliability, and water management performance, showing effective and responsive operation.

Maintenance Strategy:

Routine maintenance includes cleaning solar panels, inspecting batteries, drainage systems, tanks, and electrical connections to ensure long-term efficiency.

Sustainability Impact:

The approach is cost-effective, reduces energy and water wastage, and promotes environmental sustainability and community involvement.

Components Used in SmartEco Grid System

Sr. No.	Component Name.	QTY	Specification	Purpose
1	Solar Panel	1	12V, 20W	Generate electrical energy
2	LDR Sensor	1	Light sensitive resistor	Detect sunlight
3	LED Street Light	12	12V LED	Provide street lighting
4	Battery	1	12V Rechargeable	Store solar energy
5	Water Storage Tank	1	20 Litres	Store rainwater

IV. ADVANTAGES

Energy Saving: The system employs a light-dependent resistor (LDR) sensor to autonomously regulate street lighting according to the intensity of sunlight. This mechanism ensures that street lights do not function during daylight hours, effectively conserving electrical energy.

Water Saving: This initiative captures rainwater from the surfaces of roads and stores it for later use. This practice diminishes water waste and promotes the effective use of natural water resources.

Beneficial for Roadside Planting: The harvested rainwater is utilized for irrigating vegetation and trees situated on highway medians and along roadsides. This aids in the growth of plants and enhances the ecological conditions of the roadway infrastructure.

Self-Operated Functionality: The system operates independently, eliminating the necessity for manual intervention. This feature lessens the required human effort and reduces the potential for errors caused by human actions.

Environmentally Friendly Approach: By conserving energy and water, the system contributes to environmental preservation and encourages sustainable practices.

Economical Solution: Utilizing straightforward and inexpensive components, such as an LDR sensor and a water collection system, makes this approach cost-effective and straightforward to deploy.

V. FUTURE SCOPE

1. **Self-Regulating Irrigation System:** A smart irrigation setup can be implemented to provide water to roadside vegetation as needed, effectively minimizing water waste and enhancing plant care.



2. Water Level Surveillance System: Sensors can be placed in the water storage tank to keep track of the water level. This will aid in effective management, helping to avoid situations of overflows or drought.
3. IoT-Driven Monitoring and Management: Utilizing Internet of Things (IoT) technology allows for remote monitoring of streetlight functionality, solar energy production, and water reserves. This approach enhances system intelligence and simplifies management.
4. Rainwater Purification System: A purification system can be installed to treat collected rainwater prior to its storage. This will enhance the quality of water, expanding its potential applications.
5. Groundwater Recharge Initiative: Surplus rainwater can be channeled into recharge pits to elevate the groundwater levels, which is beneficial for civil and environmental engineering purposes.
6. Automated Source Switching Mechanism: A sophisticated automatic controller can facilitate a seamless transition between solar energy and municipal electricity, ensuring consistent operation.
7. Comprehensive Implementation: The system can be deployed along national highways, in smart cities, and urban roadways to enhance energy and water management on a broader scale.

VI. LIMITATION

1. Upfront Installation Expenses:

Setting up the system necessitates an initial expenditure for the installation of sensors, storage tanks, and pipelines.

2. Maintenance Needs:

Regular upkeep of the water storage tank and pipelines is essential to avoid issues like blockages, leaks, and contamination.

3. Limitations of LDR Sensors:

The LDR sensor functions solely based on light levels and does not register vehicle movement. Consequently, lights remain illuminated throughout the night, even in the absence of vehicles.

Specifications of LDR Sensor

Sr. No.	Parameter	Value
1	Operating Voltage	3V–12V
2	Resistance in Light	Low
3	Resistance in Dark	High
4	Function	Light Detection

VII. CONCLUSION

The SmartEco Grid – A Unified Approach for Managing Water and Energy represents an innovative and sustainable method for contemporary roadway and highway systems. This initiative incorporates automated street lighting powered by an LDR sensor along with a system for managing rainwater to support urban greenery.

In this setup, solar energy serves as the primary power source for the streetlights, significantly decreasing reliance on traditional electricity and encouraging the adoption of renewable energy sources. Additionally, a backup from the government electricity supply guarantees that streetlights remain operational even during periods of low sunlight, cloudy conditions, or if the solar system malfunctions. This enhances the system's reliability and performance.

The rainwater management feature captures precipitation from road surfaces and channels it into a storage tank. This harvested water is then repurposed for irrigating roadside vegetation and trees, contributing to water conservation efforts and promoting environmental sustainability.

From the perspective of civil engineering, this initiative is highly advantageous for road construction, stormwater management, and the development of sustainable infrastructure. It aids in energy savings, water conservation, and enhances the overall efficacy of roadway systems.

In summary, the SmartEco Grid system offers a dependable, environmentally friendly, and economical solution for integrated management of water and energy resources.



The Advanced Fingerprint Based Voting System uses biometric authentication to increase election security, accuracy, and transparency. Voter impersonation, duplicate voting, and human counting errors are common problems with traditional voting techniques. The technique guarantees that every voter is individually identifiable and only permitted to cast one ballot by incorporating fingerprint recognition technology. This improves the voting process's dependability and drastically lowers electoral fraud. Additionally, automatic vote counting and quicker result announcement are made possible by the use of electronic recording.

The system's advantages exceed its drawbacks, despite the fact that it needs adequate infrastructure, database security, and an initial investment. The solution boosts public confidence in elections through enhanced authentication procedures and safe data preservation. Future improvements like multi-biometric verification, cloud integration, and encryption can further strengthen and expand the system. All things considered, the Advanced Fingerprint Based Voting System is a cutting-edge and effective method of holding safe and fair elections.

REFERENCES

- [1]. Agarwal, A., & Narain, S. (1997). *Dying wisdom: Rise, fall and potential of India's traditional water harvesting systems*. New Delhi: Centre for Science and Environment.
- [2]. Arora, K. R. (2009). *Irrigation, water power and water resources engineering*. New Delhi: Standard Publishers Distributors.
- [3]. Duggal, S. K. (2010). *Environmental engineering*. New Delhi: New Age International Publishers.
- [4]. Ministry of New and Renewable Energy. (n.d.). *Solar street lighting system manual*. Government of India.
- [5]. Ministry of Road Transport and Highways. (n.d.). *Highway drainage guidelines*. Government of India.
- [6]. IEEE Xplore Digital Library. (n.d.). *Research papers on automatic street lighting using LDR*.
- [7]. World Health Organization. (n.d.). *Rainwater harvesting techniques and water conservation methods*. WHO Publications.
- [8]. Smart Cities Mission. (n.d.). *Smart infrastructure and smart city development reports*. Government of India

