IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

Application of IoT – Multi-Room Music System with IoT

Jyoti G. Dabhade[1], Pawan Pradip Tryambake[2], Sangharsh Sambhaji Kurhe[2]
Lecturer, Department of Information Technology [1]
Diploma Students, Department of Information Technology [2]
Government Polytechnic Awasari (Khurd), Pune, Maharashtra, India

Abstract: *The Internet of Things (IoT) enables connected devices to communicate and respond to user commands over a network. An IoT-based multi-room music system allows users to control speakers in different rooms through a common interface. This paper reviews the system's architecture, communication technologies, synchronization requirements, applications, and challenges. It examines Wi-Fi, Bluetooth, Bluetooth LE Audio, and MQTT, highlighting their different roles in audio delivery and device control. The study follows a qualitative descriptive approach based on secondary sources, including research on IoT architectures, networked audio, smart homes, and cybersecurity. No physical prototype, laboratory testing, or user survey was conducted. The review identifies synchronization, network reliability, device compatibility, and security as key challenges. It concludes with practical design considerations and future research directions for developing reliable IoT-based multi-room music systems.*

Keywords: Internet of Things (IoT), Multi-Room Audio, Smart Home, Audio Synchronization, MQTT, Wireless Networking

I. INTRODUCTION

The Internet of Things refers to connected physical devices that use sensing, processing, and network communication to exchange information or provide services. IoT concepts are increasingly applied in smart homes, where users may control lighting, climate systems, appliances, security devices, and entertainment equipment through connected interfaces [1], [2]. Audio playback is another area in which network connectivity can improve convenience.

A traditional music setup often requires a separate audio source or control arrangement for each room. A networked multi-room system can instead allow one application or central controller to select music, choose the rooms where it should play, and adjust playback settings. Depending on the design, all selected rooms may play the same content, or each room may play a different source. These capabilities can be useful in homes, cafés, hotels, offices, shops, and other spaces where audio is distributed across multiple areas.

However, playing the same music in several rooms is not only a matter of connecting speakers to a network. Small differences in playback timing can create an echo when listeners move between rooms. Network congestion, buffering, incompatible devices, weak wireless coverage, and security weaknesses may also affect the user experience. Research on IP-networked home audio has specifically identified synchronization as an important technical issue when media is delivered over networks that do not share a single clock .

This paper examines how IoT concepts can support a multi-room music system, with emphasis on architecture, communication, synchronization, applications, and implementation challenges. It is a literature-based study, not a report of a newly built or experimentally tested system.

II. PROBLEM STATEMENT

Users who want music in multiple rooms may face separate controls, limited device compatibility, inconsistent volume levels, and difficulty coordinating playback. Wireless connections can simplify installation, but a system still needs a

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429 Volume 6, Issue 5, October 2026 Impact Factor: 8.2

reliable way to discover devices, send commands, deliver audio, and coordinate playback timing. In a multi-room environment, differences in network delay and buffering can cause audible timing gaps between speakers. At the same time, connected speakers and control applications must protect user accounts, network access, and device settings from unauthorized use.

The problem addressed by this study is to understand how an IoT-based multi-room music system can provide centralized control and distributed audio playback while considering synchronization, network reliability, interoperability, privacy, and security. The study also distinguishes between control messaging and audio streaming, because a lightweight IoT messaging protocol such as MQTT is not, by itself, a replacement for an audio streaming and timing solution [4].

III. OBJECTIVES OF THE STUDY

- To explain the basic concept and purpose of an IoT-based multi-room music system.
- To describe the main components and a conceptual architecture for distributed audio playback.
- To examine communication options such as Wi-Fi, Bluetooth, Bluetooth LE Audio, and MQTT in their appropriate roles.
- To study the importance of synchronization, buffering, latency, and network quality.
- To compare the potential benefits and limitations of multi-room audio approaches.
- To identify security, privacy, compatibility, and scalability concerns.
- To outline future improvements and research opportunities for connected audio systems.

IV. RESEARCH METHODOLOGY

This paper uses a qualitative, descriptive research approach based on secondary information. Sources include published research on networked audio and IoT architectures, technical specifications, standards-body documentation, and cybersecurity guidance. The sources are used to explain system concepts and identify design trade-offs rather than to calculate a new performance result.

A. Research Design and Scope

The study examines a conceptual home or small-building audio system in which a user can control multiple playback zones through a shared interface. Its scope includes source selection, device control, local networking, audio delivery, synchronization, and basic security. It does not implement a working prototype, conduct controlled tests, collect participant responses, or claim measured improvements in audio quality, cost, or delay.

B. Sources of Information

The reviewed materials include a technical paper on synchronization strategies for IP-networked home audio [3], official MQTT documentation [4], a survey of IoT application architectures [1], a review of smart-home systems [2], Bluetooth SIG material on LE Audio [5], and NIST guidance on IoT device cybersecurity capabilities [6]. These sources provide complementary perspectives on media timing, device communication, system architecture, wireless audio, and security.

C. Analytical Framework

The material is organized around six qualitative dimensions: (1) functionality and user control; (2) audio delivery and synchronization; (3) network reliability and latency; (4) compatibility and scalability; (5) security and privacy; and (6) deployment and maintenance. These dimensions are used to compare options and derive practical design considerations.

D. Limitations of the Method

The findings depend on the selected secondary sources and are not an exhaustive systematic review of every product or standard. Commercial systems may use proprietary protocols or implementation details that are not publicly documented. As no prototype or benchmark was produced, performance statements are qualitative and should not be interpreted as experimental results.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

V. LITERATURE REVIEW

Existing research has examined the Internet of Things (IoT) from different perspectives, including smart-home applications, communication technologies, audio synchronization, device interoperability, and security challenges. The following studies and technical resources provide the foundation for understanding the development of an IoT-based multi-room music system.

A. IoT Architecture and Smart-Home Applications

Research on IoT architecture has examined how connected devices communicate and exchange information through networks, gateways, and cloud-based platforms. These architectures support remote monitoring, device management, and automation in smart-home environments. Depending on the system design, processing may take place through cloud services or locally within the home network.

Relevance to the present study: This research provides a foundation for understanding how multiple speakers and control devices can be connected and managed within an IoT-based multi-room music system.

B. Communication Technologies for IoT

Communication technologies play an important role in connecting IoT devices. MQTT is a lightweight messaging protocol based on the publish-subscribe model, making it suitable for exchanging control commands and device-status information. Bluetooth technologies also support communication between compatible devices, while Wi-Fi can provide network connectivity for connected audio devices.

Relevance to the present study: These technologies help explain how users can control speakers, manage playback commands, and coordinate devices across different rooms. However, control messaging and audio transmission are different functions and may require different communication mechanisms.

C. Audio Synchronization in Multi-Room Systems

Multi-room audio systems aim to reproduce audio across multiple speakers while maintaining synchronization between playback devices. Differences in network delay, buffering, and processing time can cause audio to reach speakers at slightly different times. Therefore, synchronization mechanisms and coordinated playback are important considerations in designing a multi-room audio system.

Relevance to the present study: This research area highlights the importance of maintaining synchronized audio playback across rooms to provide a consistent listening experience.

D. Interoperability and Device Compatibility

IoT environments may contain devices manufactured by different companies and operating through different communication protocols or software platforms. These differences can create challenges when attempting to control multiple devices through a single interface. Compatibility depends on the supported protocols, system architecture, and integration mechanisms.

Relevance to the present study: Interoperability is an important consideration when designing a multi-room music system that aims to support multiple speakers and provide centralized control.

E. Technical and Security Perspectives

Technical standards and security guidance provide important considerations for connected-device systems. The National Institute of Standards and Technology (NIST) publishes cybersecurity guidance relevant to IoT devices, including device identification, secure configuration, data protection, and access control. In a connected audio environment, security measures can help prevent unauthorized access to devices and control functions.

Relevance to the present study: This perspective supports the consideration of user authentication, secure communication, device access control, and privacy when designing an IoT-based multi-room music system.

F. Research Gap

The reviewed technical areas provide useful insights into IoT architecture, communication protocols, audio synchronization, interoperability, and cybersecurity. However, these areas address different aspects of the overall system and must be considered together when developing an IoT-based multi-room music solution.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

The present study takes a focused conceptual approach by bringing these dimensions together to examine the design considerations of a multi-room music system. It considers centralized control, communication between connected devices, synchronized audio playback, device compatibility, and security requirements. The study also recognizes that actual performance depends on the selected hardware, network conditions, supported protocols, and system implementation.

VI. CONCEPT AND ARCHITECTURE OF AN IOT-BASED MULTI-ROOM MUSIC SYSTEM

A. Basic Concept

A multi-room music system divides a building into playback zones. A zone may represent a bedroom, living room, kitchen, office, or other area. A user chooses the audio source and one or more zones from a mobile application, web interface, voice interface, or physical controller. Each selected playback device receives the media or a stream reference and plays audio through its connected speaker.

The system may operate in two common modes. In synchronized mode, selected rooms play the same program and should remain aligned in time. In independent mode, different rooms can play different content or use separate volume settings. The second mode requires flexible source and session management; the first places stronger demands on timing coordination.

B. Main Components

Component	Role
Audio source	A phone, computer, local media library, streaming service, or other permitted source that provides the selected content.
Control interface	An application or controller used to select rooms, start or stop playback, adjust volume, and view device status.
Network and router	The local network connects the controller and playback devices. Wi-Fi is a common option for networked speakers because it can carry control data and audio traffic.
Playback nodes	Network-capable speakers or audio receivers that receive media, buffer it, decode it, and output sound.
Coordination service	Software that manages room groups, playback state, timestamps, buffering targets, and recovery when a device falls behind.
Optional cloud service	A service that may support remote access, accounts, discovery, or music-service integration. Local playback should be designed thoughtfully if internet access is interrupted.

C. Typical Operating Sequence

The user opens the control application and selects an available audio source.
The application discovers or retrieves the list of supported playback devices and rooms.
The user chooses one room or a group of rooms and sends a playback command.
The coordinator distributes the required control information and media instructions to the selected devices.
Each playback node prepares a buffer and follows the timing information provided by the system.
Devices report status such as connected, playing, paused, or unavailable; the controller updates the interface and handles errors.

D. Communication and Media Delivery

A practical design separates control-plane communication from media-plane delivery. The control plane carries relatively small messages, including playback commands, room grouping, volume settings, and device health. MQTT can be considered for this role because it uses a lightweight publish/subscribe model [4]. The media plane carries the

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

actual audio and requires a transport, codec, buffering strategy, and timing mechanism appropriate to the product. Using a messaging protocol for control does not by itself solve audio streaming or synchronization.

VII. COMMUNICATION TECHNOLOGIES AND SYNCHRONIZATION

A. Wi-Fi and IP Networking

Wi-Fi and IP networking are widely used in connected-home environments and can support communication between a controller, router, and network-capable playback devices. A shared local network can simplify room grouping and allow audio sources to be managed centrally. However, real performance depends on signal strength, interference, router capacity, traffic from other devices, and the implementation of the audio system. A system should avoid assuming that a strong internet connection guarantees a strong local wireless link.

B. Bluetooth and Bluetooth LE Audio

Bluetooth is useful for short-range audio links and simple device pairing. Bluetooth LE Audio adds capabilities including unicast and broadcast audio in compatible devices [5]. Its suitability depends on whether the source and receivers support the required specifications and operating mode. Bluetooth range and device-group behavior may differ from a Wi-Fi-based whole-home audio design, so the technologies should be evaluated against the actual number of rooms, distances, and playback requirements.

C. MQTT for Device Control

In a possible design, the controller publishes a command to a topic associated with a room or device group, and subscribed devices receive the command. Status messages can travel back to the controller. This model can help decouple the user interface from individual device implementations. Authentication, topic permissions, encrypted transport, and sensible failure handling are still required. MQTT is best described here as a potential control-message mechanism, not as a universal multi-room audio standard [4].

D. Why Synchronization Matters

Network packets can experience different delays, and devices may use separate clocks. If one speaker starts earlier than another, listeners in adjacent rooms may hear the same sound at different times. A synchronization design may use shared timestamps, clock-drift correction, controlled buffering, and scheduled playback. Buffering helps absorb short-term network variation, but larger buffers can increase the delay between a user command and audible playback. The design must balance stable synchronization with acceptable responsiveness [3].

E. Reliability and Recovery

A robust system should define what happens when a speaker disconnects, the router restarts, or a stream becomes unavailable. Possible measures include reconnecting automatically, resuming from a known playback position, notifying the user, and preventing a recovered device from rejoining a group at the wrong time. These behaviors should be tested under different network conditions before the system is considered reliable.

VIII. COMPARATIVE ANALYSIS

The technologies below serve different purposes. They are not direct substitutes in every scenario; the best choice depends on whether the priority is whole-home networking, short-range audio, lightweight control, or device interoperability.

Technology	Potential role	Key limitation
Wi-Fi / IP networking	Connects controllers and networked playback devices; can carry media and control traffic.	Coverage, congestion, router performance, and device compatibility can affect reliability.
Bluetooth Classic audio	Convenient short-range audio connection to compatible receivers.	Range and group behavior may limit multi-room layouts; multi-device support varies by product.
Bluetooth LE Audio	Supports defined unicast and broadcast	Requires compatible source and receiving

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

	audio scenarios in compatible devices.	devices; support must be checked per product.
MQTT	Lightweights publish/subscribe messaging for commands and status in an IoT architecture.	Not a complete audio streaming or synchronization solution by itself.

IX. RESULTS AND DISCUSSION

The qualitative comparison indicates that a multi-room music system is best understood as a combination of audio delivery, device control, and synchronization rather than as a single IoT protocol. A shared application can simplify user interaction, while room groups and device-status feedback can improve manageability. Networked playback is technically plausible using existing technologies, but the exact behaviour depends on the architecture and compatibility of the chosen devices.

Synchronization emerges as a central design requirement when several rooms play the same program. Sending a play command to every speaker is not sufficient if each device begins decoding at a different time. A suitable implementation must coordinate playback timing and handle clock drift and network variation. This aligns with the issues identified in research on IP-networked home audio [3].

The analysis also shows that communication technologies should be assigned clear roles. Wi-Fi/IP networking may form the local connection between devices; Bluetooth or Bluetooth LE Audio may suit particular direct or broadcast audio use cases; and MQTT may provide lightweight control messaging. A design that treats these technologies as interchangeable risks overlooking their different purposes and constraints [4], [5].

Security and maintainability are equally important. A connected speaker should not expose unrestricted control interfaces or accept commands from unknown users. Device identity, secure configuration, data protection, controlled software updates, and access restrictions are useful baseline considerations [6].

These findings are conceptual. Because this paper does not include a prototype, benchmark, or user study, it cannot establish a numerical improvement in latency, energy consumption, sound quality, or cost. Those outcomes would need to be measured in a future implementation.

X. CHALLENGES AND LIMITATIONS

A. Technical Challenges

Synchronization: Maintaining close timing across devices with different clocks and buffering behavior.

Network quality: Managing weak coverage, interference, congestion, and packet loss.

Latency: Balancing smooth playback against the delay introduced by buffering and coordination.

Interoperability: Supporting devices with different discovery, control, codec, and media protocols.

Scalability: Maintaining manageable traffic and reliable control as more rooms and playback nodes are added.

Power and energy: Considering standby consumption, wireless activity, and the energy cost of always connected devices.

B. Security and Privacy

A multi-room system may be connected to a home account, local network, and third-party music services. Weak passwords, outdated firmware, insecure configuration, or excessive permissions could allow unauthorized playback or changes to device settings. Recommended safeguards include unique device identity, authenticated control, encrypted communication where supported, restricted interfaces, secure updates, and clear account-management options. These measures are consistent with the general IoT device security capabilities described by NIST [6].

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

C. Practical and Cost Limitations

Installation cost depends on the number and type of speakers, amplifiers, networking equipment, and software services. Existing speakers may require additional receivers or adapters. Users may also need technical support when changing routers, adding rooms, or connecting devices from different manufacturers. A system that relies heavily on a cloud service may lose some functions during an internet outage, even when the local network remains available.

D. Limitations of the Present Study

This paper is based on secondary literature and publicly available technical documentation. It does not compare specific commercial products, inspect proprietary implementations, test audio synchronization, measure power use, or survey users. Therefore, the discussion identifies design considerations and plausible trade-offs but does not claim experimentally verified system performance.

XI. FUTURE SCOPE

Future work may develop and evaluate a prototype using several playback nodes connected through a local network. Tests could measure start-time difference, long-term synchronization drift, response time to pause and volume commands, recovery after disconnection, and behaviour under different levels of network congestion. These measurements would provide evidence beyond the qualitative discussion in this paper.

Further work could explore local-first control so that core playback functions remain available without internet access. Edge processing may help reduce dependence on remote services for time-sensitive tasks [1]. Interoperability can be improved through clearly documented interfaces and standards-based device discovery. Security could be evaluated through threat modelling, access-control testing, firmware-update checks, and review of data collection practices.

Other possible extensions include voice control, accessibility features, personalized volume limits, scheduled playback, energy-aware standby modes, and support for public or commercial environments. Any use of automated recommendations or user profiles should be designed with transparent privacy controls. These are potential future directions, not features demonstrated by the present study.

XII. CONCLUSION

An IoT-based multi-room music system can provide centralized management of audio playback across several rooms by combining a control interface, network connectivity, playback devices, and coordination software. The literature reviewed in this paper suggests that the main design challenge is not simply connecting speakers, but coordinating reliable audio delivery and synchronized playback while maintaining interoperability and security.

Wi-Fi/IP networking, Bluetooth LE Audio, and MQTT can contribute to different parts of a solution, but they serve different roles and should not be treated as interchangeable. In particular, lightweight IoT messaging can manage commands and status, while media delivery requires a suitable audio transport and timing strategy. Device security, reliable recovery, and user-friendly configuration are also essential for practical adoption.

Since this study uses secondary sources only, its conclusions are conceptual and do not represent experimental validation. A future prototype with repeatable timing, network, usability, and security tests would help determine how well a specific implementation performs in real environments.

REFERENCES

[1] A. Dauda, O. Flauzac, and F. Nolot, “A Survey on IoT Application Architectures,” Sensors, vol. 24, no. 16, article 5320, 2024. doi: 10.3390/s24165320.

[2] S. Chakraborty et al., “Smart Home System: A Comprehensive Review,” Journal of Electrical and Computer Engineering, 2023, article 7616683. doi: 10.1155/2023/7616683.

IJARSCT
International Journal of Advanced Research in Science, Communication and Technology
International Open-Access, Double-Blind, Peer-Reviewed, Refereed, Multidisciplinary Online Journal
ISSN: 2581-9429
Volume 6, Issue 5, October 2026
Impact Factor: 8.2

[3] T. Blank and R. Atkinson, "Synchronization Strategies for IP Networked Home Audio Equipment," Audio Engineering Society, UK 20th Conference: Convergence, paper 13, pp. 13:1–13:11, Mar. 2005. Available: https://aes.org/publications/elibrary/elibrary-page/?id=17257

[4] OASIS MQTT Technical Committee, "MQTT Specifications," MQTT.org. Available: https://mqtt.org/mqtt-specification/ (accessed Oct. 24, 2026).

[5] Bluetooth Special Interest Group, "Bluetooth LE Audio FAQs," Bluetooth Technology Website. Available: https://www.bluetooth.com/media/le-audio/le-audio-faqs/ (accessed Oct. 24, 2026).

[6] M. Fagan, K. N. Megas, K. Scarfone, and M. Smith, "IoT Device Cybersecurity Capability Core Baseline," NIST Interagency/Internal Report 8259A, National Institute of Standards and Technology, May 2020. doi: 10.6028/NIST.IR.8259A.

[7] IEEE 802.11 Working Group, "Wireless Local Area Networks," IEEE. Available: https://www.ieee802.org/11/ (accessed Oct. 24, 2026).

[8] Digital Living Network Alliance, "DLNA Certified Product Classes and Capabilities," DLNA Product Search. Available: https://product.dlna.org/ (accessed Oct. 24, 2026).