

Volume 2, Issue 2, June 2022

Assessment of Environment, Health and Safety (EHS) Management Plan by Risk Assessment of Activities in Construction Project Work

Pravin Tathod¹ and Prabhanshu Jain²

Assistant Professor¹ and PG Scholar²

Fire Technology & Safety Engineering Department, IPS Academy Institute of Engineering & Science, Indore^{1,2}

Abstract: The building construction industry is growing all over the world. The construction industry is an important part of the economy in many countries and is often seen as a driver of economic growth especially in developing countries. Owing to its relatively labour-intensive nature, construction works provide opportunities for employment for a wide range of people skilled, semi-skilled and unskilled. This study, therefore, aims to find out the current practice of health and safety risk assessment, risk communication and risk control and improving the Environment Health and Safety management plan for the Construction project site. In pursuing this objective, the case study strategy was adopted whereby a construction site is selected through convenience sampling. This research contributes significantly to construction safety management SHAPOORJI PALLONJI AND COMPLANY PVT. LTD. and can be utilized to analyse and manipulate the safety risk level of every possible hazardous event that is identified during the construction period. The proposed model could also be applied in other construction projects to obtain results with greater accuracy and reliability from the evaluation and ranking of safety risks, which would yield data that would be useful in helping the management team to mitigate and control the risks in other construction projects.

Keywords: Health and safety risk, Risk Management, Risk Communication, Risk control, Construction Sites, Practice, and Process

I. INTRODUCTION

Project management is the science which applies skills, tools and techniques to fulfil project activities in a way that the expectations and requirements of stakeholders are fulfilled or exceeded. Project risk management is an integral part of the process which aims at identifying the potential risks associated with a project and responding to those risks. It includes activities which aim to maximize the consequences associated with positive events and to minimize the impact of negative events. It is believed generally that risk in an environment is a choice rather than fate, and the inherent uncertainty in the plans can affect the desired outcome of achieving project and business goals [1]. Risk is present in all the activities in a project; it is only the amount which varies from one activity to another.

Variations are inevitable on building and civil engineering projects and may range from small changes having little consequential effects to major revisions, which result in considerable delay (or) disruption to the project [4]. There are a number of reasons for the introduction of changes on construction works including:

- 1. Inadequate briefing from the client
- 2. Inconsistent and late instructions from the client
- 3. Incomplete design
- 4. Lack of meticulous planning at the design stage
- 5. Lack of co-ordination of specialist design work
- 6. Late clarification of complex details

Additionally on civil engineering works there are many cases where changes and new rates are necessary because of the nature of the ground [2]. Furthermore, changes may occur due to the client's desire to incorporate the latest technology into the project which will led to deviations of time and cost of the project which indicate the risk in the project [3]. The

Copyright to IJARSCT www.ijarsct.co.in

IJARSCT



International Journal of Advanced Research in Science, Communication and Technology (IJARSCT)

Volume 2, Issue 2, June 2022

current study is focused on concepts of all types of risk management at the construction site of SHAPOORJI PALLONJI AND COMPLANY PVT. LTD. and will cover the related literature on the topic.

1.1 Concept of Risk Analysis

The concept of risk is multi-dimensional. In the context of construction industry, the probability that a definite factor detrimental to the overall project occurs is always present. A lack of predictability related to the consequences of a planning situation and the associated uncertainty of estimated outcomes leads to the consequence that results can either be better than expected or can be worse [5]. In addition to the different definitions of risks, risks can be categorized for different purposes as well. The broad categories of construction risks are external risks and internal risks; while some other categories curtail risks as political, social and safety risk etc.

- 1. Project Risk
- 2. Determination of Risk
- 3. Factors affecting Risk
- 4. Types of Risks
- 5. Common sources of risk in construction projects
- Major processes of Project Risk Management 6.
- 7. Response to Risk
- Advantages of Risk Management 8.
- 9. Limitations of Risk Management




Figure 1 Designed Frame of Working [6]

1.2 Definitions of Key Terms

The field of risk management is faced with difficulties in defining and agreeing on principles. Risks are dealt with differently across different countries, industries and sectors and fields. Terms, definitions and interpretations are as varied as the number of sources providing them. There are no agreed unified definitions of risk, risk analysis, assessment and management. There are often misconceptions. Different terms, for example "risk analysis" and "risk assessment", are often used interchangeably [8].

- 1. Health: Health is the general condition of a person in mind, body and spirit, usually meaning to be free from illness, injury or pain.
- 2. Safety: Safety is related to external threats, and the perception of being sheltered from threats. According to the business Dictionary, safety is defined as a relative freedom from danger, risk, or threat of harm, injury, or loss of personnel and/or property, whether caused deliberately or by accident.
- 3. Hazards: A hazard is the potential for harm. In practical terms, a hazard is often associated with a condition or activity that, if left uncontrolled, can result in an injury or illness.
- 4. Risk: Risk has been traditionally defined as a measure of the probability and severity of adverse effects [9].

$$RISK = S \times P \times C$$

Where, S = Scenario leading to hazard, P = Probability of occurrence, C = Consequence (severity) DOI: 10.48175/IJARSCT-5606

Copyright to IJARSCT www.ijarsct.co.in



Volume 2, Issue 2, June 2022

- 5. Accident and Injury: The terms accident and injury refer to separate phenomena, mutually interrelated as cause and effect (exposure and outcome) [10].
- 6. **Risk Assessments:** The Health and Safety Executive (HSE), defined risk assessment as a process that identifies the hazards associated with particular activities/tasks, evaluates the effects of exposure to these hazards and implements the measure needed to control the risk of injury/ill health to as low a level as possible.
- 7. Risk Management: Risk management is an integral component of good management and decision-making at all levels. In construction having a perception of risk management is an integral part of construction management.
- 8. Risk Communication: The notion of risk communication refers to a social process by which people become informed about hazards, are influenced to change their behaviour and are enabled to participate in decision-making about risk issues [11].
- **9. Risk Control:** Risk control is a technique that utilizes findings from risk assessments (identifying potential risk factors in a firm's operations, such as technical and non-technical aspects of the business, financial policies, and other policies that may impact the well-being of the firm), and implementing changes to reduce risk in these areas.

II. LITERATURE REVIEW

Akintoye et.al [12] The paper describes, based on a questionnaire survey of general contractors and project management practices, the construction industry's perception of risk associated with its activities and the extent to which the industry uses risk analysis and management techniques. It concludes that risk management is essential to construction activities in minimizing losses and enhancing profitability.

Bing & Tiong et.al [13] The current Asian financial crisis has put the role of risk management in the construction business into focus. For firms engaging in the international construction business, one of the most effective means of mitigating financial risks is through a joint venture (JV) with a local partner. **Daniel et.al [14]** This paper discusses the core issues of global risk factors modelling, assessment and management. The research reported upon forms part of a larger study that aims to develop a fuzzy decision framework for contractors to handle global risk factors affecting construction cost performance at a project level. [15] Major global risk factors affecting cost performance were identified through an extensive literature review and preliminary discussions with construction contractors.

Hastak M. et.al [16] This paper presents a risk assessment model for international construction projects. The International Construction Risk Assessment Model (ICRAM-1) assists the user in evaluating the potential risk involved in expanding operations in an international market by analysing risk at the macro (or country environment), market, and project levels.

Akintoye et.al [17] The paper describes, on the basis of a questionnaire survey of general contractors and project management practices, [18] the construction industry's perception of risk associated with its activities and the extent to which the industry uses risk analysis and management techniques.

Emmanuel Eze et.al [19] The complex networks of activities of construction projects have made the construction environment unfriendly and unsafe for the construction tradespeople.

III. COMPANY DOMAIN

SHAPOORJI PALLONJI AND COMPLANY PVT. LTD. has a rich history spreading over 154 years in the construction industry in India as well as global market. Today SP group has a presence in around 60 countries worldwide, with a more entrenched presence in Middle East and Africa since 1971 when we constructed the palace of HM Sultan Qaboos. A growing workforce of around 40,000 employees from across more than 20 nationalities contribute daily towards the share vision of SP Group. Each company and its employees have further strengthened the foundation of trust that SP Group was built upon. The Shapoorji Pallonji Group is a dynamic enterprise which draws vital support from its various individual entities to be able to execute turnkey projects, swiftly and efficiently.



Volume 2, Issue 2, June 2022



Figure 2 Shapoorji Pallonji and Company PVT. LTD. [23]

IV. PROBLEM IDENTIFICATION AND SYSTEM DOMAIN

Safety is a basic physical and psychological need of human beings. Every day some 950 people die and over 720,000 workers get hurt because of occupational accidents. Annually, over 48,000 workers die because of occupational accidents in India and there are almost 37 million occupational accidents which causes at least 4 days' absences from work [25]. In terms of economics, the International Labour Organization (ILO) has estimated that the total costs of occupational accidents and work-related diseases are 4% of the gross national product (GNP). The total GNP of the world was approximately 84.54 trillion USD in 2020 (World Bank 2020) which means that worldwide the annual cost of work-related nijuries and diseases is approximately 3.3 trillion USD (0.04x 84.54).

4.1 Identification of Problems at SPCPL Constructions

Construction sites are among the hazardous places where injuries and fatalities of workers commonly happen. The EHS issues are giving a bad image to the socio-economic importance of the construction industry. The cruel fact is that most of the accidents are unnecessary which could have been protected if the principles of OSH had been implemented at workplaces.

In the absence of properly compiled data, the scale of EHS problems may not be well understood. If the causes leading to occupational accidents and injuries at construction sites are not identified and awareness of EHS issues is not created to the stakeholders of the construction sector, the problems will continue to significantly affect the construction sector as well as the socio economy of the country.

This study therefore attempts to address such issues and hence it is expected to reduce consequential effect of occupational accidents, injuries and fatalities.

S.No	Detail	Values
1.	Total Safe Man Hours – December- 2021	22,19,496
2.	Cumulative Safe Man Hours – FY # 2021-22	24,96,45,304
3.	No. of Reportable Injuries – FY # 2021-22	6
4.	Nos. of Minor Injuries – FY # 2021-22	11
5.	Cumulative Incident Rate	0.11
6.	Cumulative Frequency Rate	0.04
7.	Cumulative Severity Rate	240.37
8.	HSE Walk conducted- Feb- 2021	100%
9.	HSE Committee Meetings Conducted - Feb- 2021	100%
10.	HSE Training Conducted, Training Man Hours -Feb- 2021	10042
11.	Total First Aid Report- Feb- 2021	74
12.	Total Near Miss – Feb- 2021	13
13.	Unsafe Work Stoppage Notifications Issued- Feb- 2021	16
14.	Warring Letters/Memos issued at Project Level -Feb- 2021	48
15.	Projects Audited by Regional HSE Team & Audit reports issued - Feb- 2021	8

Table 1 Regional HSE Score Card of Shapoorji Pallonji & Co. Pvt. Ltd.

IJARSCT



International Journal of Advanced Research in Science, Communication and Technology (IJARSCT)

Volume 2, Issue 2, June 2022

4.2 Reasons behind Past Accidents

- 1. Electrical Activity
- 2. Hot Work
- 3. Material Handling
- 4. Scaffolding
- 5. Shuttering
- 6. Height Work
- 7. Concreting
- 8. Vehicle Movement
- 9. Sudden Breakdown maintenance equipment.
- 10. Welding & Cutting
- 11. Use of Lifting Equipment
- **12.** Painting & coating Work
- **13.** Concrete pump
- 14. Ladder
- 15. Bar bending & Cutting
- 16. Storage of Flammable material
- **17.** Tower Crane

V. RESEARCH METHODOLOGY

This chapter presents the research strategy used in this study. It reviews the basic research approaches available, which include the quantitative, qualitative and mixed methods approach. Thereafter the chapter discusses the method opted in this study and its justification. The research design is illustrated followed by a discussion of case selection and the methods used for data collection.

- Brain storming
- Delphi technique
- Interview /expert opinion
- Past experience
- Check lists
- Influence diagram
- Flow chart
- Cause-and-effect diagrams

This system classifies the trades by the principal skills inherent in the trade below: -

Table 2 Hazards Distribution [34]				
S. No	Occupation	Types of HAZARDS		
1.	Brick masons	Cement dermatitis, awkward postures, heavy loads		
2.	Stonemasons	Cement dermatitis, awkward postures, heavy loads		
3.	Hard tile setters Vapour from bonding agents, dermatitis, awkward postur			
4.	Carpenters Wood dust, heavy loads, repetitive motion			
5.	Drywall installers	Plaster dust, walking on stilts, heavy loads, awkward postures		
6.	Electricians	Heavy metals in solder fumes, awkward posture, heavy loads		
7.	Electrical power installers and repairers	Heavy metals in solder fumes, heavy loads		
8.	Painters	Solvent vapours, toxic metals in pigments, paint additives		
9.	Plasterers	Dermatitis, awkward postures		
10.	Plumbers	Lead fumes and particles, welding fumes		
11.	Pipefitters	Lead fumes and particles, welding fumes		
12.	Steamfitters	Welding fumes		



IJARSCT

13. Carpet layers Knee trauma, awkward postures, glue and glue vapour 14. Soft tile installers Bonding agents 15. Concrete and terrazzo finishers Awkward postures 16. Glaziers Awkward postures Insulation workers 17 Synthetic fibres, awkward postures Paving, surfacing and tamping Asphalt emissions, gasoline and diesel engine exhaust, heat 18 equipment operators Rail- and track-laying equipment Silica dust, heat 19 operators 20 Roofers Roofing tar, heat, working at heights 21 Sheet metal duct installers Awkward postures, heavy loads, noise 22 Structural metal installers Awkward postures, heavy loads, working at heights 23 Welders Welding emissions 24 Solders Metal fumes, lead, cadmium 25 Drillers, earth, rock Silica dust, whole-body vibration, noise 26 Noise, whole-body vibration, silica dust Air hammer operators 27 Pile driving operators Noise, whole-body vibration 28 Hoist and winch operators Noise, lubricating oil 29 Crane and tower operators Stress, isolation Excavating and loading machine Silica dust, histoplasmosis, whole-body vibration, heat stress, 30 operators noise

Volume 2, Issue 2, June 2022

5.1 Methodological Detail

The research work started with problem identification. The problem identification is done through literature review and discussions with professionals in the construction industry. The nature of the research is explorative, and the research methodology comprises three stages as stipulated below.

- 1. Stage 1: Identifying the status of EHS management in the construction industry by conducting literature review and discussions with professionals in the industry.
- 2. Stage 2: Then analysis and discussion are conducted to draw conclusions
- **3. Stage 3:** Designing the Risk assessment of different project sites and updating EHS plan for a construction site based on literature review and discussions and forward recommendations based on the findings of the study and the reviewed literatures.

In the construction industry, risk can be defined in relation to occupational accidents leading to fatal incidents. Risk [29] is intrinsic in all project undertakings, as it can never be fully eliminated, although it can be effectively managed to mitigate the impacts on the achievement of the objective of the project. Other definitions of risk are available in the literature, for example, "the traditional view of risk is negative, representing loss, hazard, harm and adverse consequences" and "the underlying condition that can generate a possible risk event at some time forward from the point of decision-making". [38] state that the impact of risk can be measured as the probability of a specific unwanted event and its unwanted consequences or loss:

$RM = RL \times RS$

Where, RM = Risk magnitude; RL = Risk likelihood; RS = Risk severity

VI. MATHEMATICAL MODEL AND REPORT

Project work has been done in four steps. First attempt is to understand every step for construction of bridge i.e., survey, design, planning, resource assembling, pilling, pile cap, cofferdam work, pier and pier cap and erection works. Second step is to develop a 4x4 matrix for risk analysis as per IMS manual, then EHS Risk assessment done by matrix method for every activity. Then gap analysis is done by Data collection, data analysis, Employee survey, EHS walk down, evaluate findings and suggest improvement.



IJARSCT

Volume 2, Issue 2, June 2022




Figure 3 Data Collection Techniques Table 3 Data Collection Matrix

C.					
S. N o	System	Variable	Method	Data	
1.	Institutional system	Regulations	Interviews, documentary review	Legal practices in health and safety risk management.	
		Institutional Structure	Interview	Power relations: management,	
		Control mechanism	Interviews, documentary review	Control methods and enforcement technique.	
		Management style	Interview	Involvement, resource allocation	
2.	Organisation system	Structure	Interviews, documentary review	Organisation structure, power relation	
2.		Company policy	Interviews, documentary review	Health and safety policy	
		Communication	Interview	Methods/ tool and	
				Communication channel	
	Individual system at construction sites	Education, Experience	Interview	Demographic information	
		Perception	Interview	Feeling about the risk	
3.		Responsibility	Interview and observation	Different roles of individuals regarding risk assessment, communication and control	
4.	Work Environment	Workingtools/methodsWorkWorkingProcedurePhysicalspace	Observation	Methods of working Team cooperation Working procedures Site space.	

The chapter discussed the approaches to research, namely, the quantitative method. This study opted to use the case study method to achieve its objective. The justification for using the case study to gather empirical data was discussed. The



Volume 2, Issue 2, June 2022

research design was also shown to have part by part comprising an extensive literature review and the conducting of a pilot study and part being the main fieldwork, whereby each case would be analysed, there would be a cross-data analysis and, last but not least, the conclusion would be provided. The next chapter discuss the empirical finding from study as their results.

VII. RESULTS AND DISCUSSIONS

This chapter presents the nature of health and safety risk on construction sites ITPO PRAGATI MAIDAN and provides an overview of how site managers, supervisors and workers perceive those risks. The first part of this chapter provides the results from the interviews held with five site managers on the types and sources of accidents and ill-health problem on ITPO PRAGATI MAIDAN construction sites. The second part provides the results from the questionnaire survey of site managers, gang supervisors and workers on how they perceive the health and safety hazards identified by the interview survey.

Table 4 Health and safety hazard consequences as ranked by site managers [50]			
S. No	Type of health and safety hazards consequences Rate		
1.	Falling from height	8	
2.	Hit by falling object, trips and fall	7	
3.	Back pain, muscular pain, due to manual handling	6	
4.	Health problem caused by chemicals	5	
5.	Health problem caused by dust	5	
6.	Health problem caused noise	5	
7.	Crushed moving equipment, cuts by equipment and hand-led tools	4	
8.	Health problem caused by too long bending and twisting	4	
9.	Injury from fire and other disaster	3	
10.	Covered by earthwork during excavation of basement and trenches	2	
11.	Bullying and stress	1	

Table 4 Health and safety hazard consequences as ranked by site managers [50]




Figure 4 Employers on the construction sites




Figure 5 Nature of employment on construction sites

7.1 Risk Perception

Site managers, gang supervisors and workers were asked to indicate qualitatively the probability of health and safety problems occurring when working in a hazardous situation. The Likert scale was used where 1 = very likely to occur, 2 likely to occur, 3 = moderate, 4 = not likely to occur, and 5, Not likely to occur at all (never). The results are as indicated in Figures 6 and 7



IJARSCT

International Journal of Advanced Research in Science, Communication and Technology (IJARSCT)

Volume 2, Issue 2, June 2022




Figure 6 Risk perception of the workers




Figure 7 Risk perception of the Supervisor

7.2 Hazard Consequences Categorization

This categorization is performed so as to determine which hazard consequence is perceived as higher by both group supervisors and workers. In hazard categorization, hazard consequence was calculated according to the number of respondents who indicated that the probability of occurrence was very likely to occur and likely to occur. The results have been grouped into categories. Category A indicates hazards consequence highlighted by over 150 respondents. Category B contains hazard consequences highlighted by 100-149 respondents. Category C represents hazards consequences mentioned by 50-99 respondents, and Category D contains hazard consequences mentioned by under 50 respondents. The results are indicated in Table below.

S.	HAZARD CONSEQUENCES	RESPONDENT	CATEGORY	
NO				
1.	Fall From Height	171	A	
2.	Hit by Falling objects, trip and falls	152	Α	
3.	Back and Muscles pain due to Manual Handling	126	В	
4.	Crushed by Moving objects/cuts by tools	118	В	
5.	Health problem due to Noise	107	В	
6.	Health problem due to Dust	71	С	
7.	Health problem due to Bending or Twisting	36	D	
Table 5 RISK PRIORITY INDICATOR				

Table 4 Hazards consequences category as perceived by workers and supervisors

Severity /	Insignificant	Slightly	Harmful	Very	Extremely
Likelihood	(1)	Harmful (2)	(3)	Harmful (4)	Harmful (5)
Highly Unlikely (1)	TRIVIAL (1)	TRIVIAL (2)	TOLERABLE (3)	TOLERABLE (4)	MODERATE (5)
UNLIKELY	TRIVIAL	TOLERABLE	MODERATE	MODERATE	SUBSTANTIAL
(2)	(2)	(4)	(6)	(8)	(10)
LIKELY	TOLERABLE	MODERATE	MODERATE	SUBSTANTIAL	SUBSTANTIAL
(3)	(3)	(6)	(9)	(12)	(15)
VERY LIKELY (4)	TOLERABLE (3)	MODERATE (8)	SUBSTANTIAL (12)	SUBSTANTIAL (16)	INTOLERABLE (20)
CERTAIN (5)	MODERATE (5)	SUBSTANTI AL (10)	SUBSTANTIAL (15)	INTOLERABLE (20)	INTOLERABLE (25)



Volume 2, Issue 2, June 2022

The results presented above provided an outline of the nature of health and safety risks on PRAGATI MAIDAN construction sites. The main health and safety hazards include working at a height, falling objects, manual handling hazards, noise, dust and bending and twisting and equipment. Workers and supervisors were asked to indicate their perception of identified hazards based on the probability of occurrence of the hazard consequences. Among these hazards' consequences, falling from a height and muscle and back pain due to manual handling were perceived to be highly likely by workers and supervisors, while crushed by a moving object and health problem due to too much bending and twisting were perceived to be less likely.

VIII. CONCLUSION AND RECOMMENDATION

This study aimed to ascertain the current practice of health and safety risk management on ITPO PRAGATI MAIDAN construction sites, focusing on risk assessment, risk communication and risk control. In pursuing this objective, the case study strategy was adopted, with a holistic view of health and safety risk assessment, risk communication and risk control on construction sites.

The study revealed that the responsibility for construction site health and safety lies with the main contractor, resulting in many designers, consultants and clients absolving themselves from responsibility if accidents occur on the site. The active participation of clients and design teams in the built environment in health and safety matters is yet to be realised. Meanwhile an appropriate procurement practice that promotes the adoption of good health and safety risk management is an issue.

The study also revealed that no systematic methods were used, but risk was assessed by brainstorming, checklists and health and safety regulations. Judgement of risk was based on individual judgement assisted by experience, educational background and knowledge of health and safety regulations. Working at height and manual handling observed to be most critical hazards in construction sites.

Based on methods used to communicate risk at construction sites, it was revealed that toolbox meetings, site meetings, posters and informal verbal communication are used to communicate risk. It was also revealed that safety committees and gang supervisors play a major role in communicating health and safety risks. However, the issue of power relations and conflicts was observed when there is a clear separation between health and safety communication and quality and productivity. The study also reveals that PPE is the main item used for risk control.

8.1 Recommendations

- 1. Implication for Policy, Regulatory System and Industry
- 2. Implication for the Organisations
- 3. Implication for the Professionals concerned with Project Management

REFERENCES

- [1]. A. S. Akintoye and M. J. Macleod, "Risk analysis and management in construction" 1997.
- [2]. T.E. Uher and A.R. Toakely, "Risk management in conceptual phase of a project,"1999.
- [3]. L. Bing and R. L.K Tiong, "Risk management model for international construction joint ventures,"1999.
- [4]. M. Hastak and Shaked, "ICRAM-1 Model for internation al construction risk management,"2000.
- [5]. S. Q. Wang and M. F. Dulami, "Risk management frame work for construction projects in developing countries,"2004.
- [6]. Rwamamara, A.R. (2007). Planning the Healthy Construction Workplace through Risk Assessment and Design Methods, Doctoral thesis Lulea University of Technology, Department of Civil, Mining and Environmental Engineering
- [7]. Charles, M., Pillay, J. and Ryan R. (2007). Guide to Best Practice for Safer Construction: Literature review 'From concept to completion, Cooperative Research Centre for Construction Innovation, for Icon.Net Pty Ltd.
- [8]. Lingard, H and Rowlinson, S M. (2005). Occupational Health and Safety in construction project management; UK Taylor & Francis.
- [9]. Haimes, (2009). Risk Modeling, Assessment, and Management, (3rd Edition) John Wiley and Sons, Ney Jersel Canada.



Volume 2, Issue 2, June 2022

- [10]. Andersson, R. (1999). Injury Causation, Injury Prevention and Safety Promotion Definitions and Related Analytical Frameworks. In: Safety Promotion Research, Laflamme, L., Svanström, L. and Schelp, L. (Eds.) 15-42. Karolinska Institutet, Stockholm.
- [11]. Bohrmann, B. (2000). A Socio-Psychological Model for Analyzing Risk Communication Process; The Australian Journal of Disaster and Trauma studies; 2000.
- [12]. Akintoye and MacLeod (1997), Risk analysis and management in construction, International Journal of Project Management, Volume 15, Issue 1, 1997, Pages 31-38, ISSN 0263-7863
- [13]. Bing, L., & Tiong, R. L. (1999). Risk management model for international construction joint ventures. Journal of Construction Engineering and Management, 125(5), 377-384
- [14]. Daniel & Andrew (2003), Modelling global risk factors affecting construction cost performance, International Journal of Project Management, Volume 21, Issue 4, Pages 261-269, ISSN 0263-7863
- [15]. E. Osipova Thesis (2008), "Risk management in construction projects" a comparative study of the different procurement options in Sweden", Licentiate dissertation, Lulea
- [16]. Hastak, M., & Shaked, A. (2000). ICRAM-1: Model for international construction risk assessment. Journal of management in engineering, 16(1), 59-69.
- [17]. Jayasudha, K., and B. Vidivelli. "A Study on Risk Assessment in Construction Projects." International Journal of Modern Engineering Research (IJMER) Vol 4.
- [18]. Devdatt P Purohit, Dr.N A Siddiqui, Abhishek Nandan & Dr.Bikarama P Yadav: Hazard Identification and Risk Assessment in Construction Industry: International Journal of Applied Engineering Research: ISSN 0973-4562: Volume 13, Number 10:2018.
- [19]. Emmanuel Eze, Onyinye Sofolahan, Lawrence Siunoje: Health and safety management on construction projects: the view of construction trades people: Journal of Infrastructure Development: 2020
- [20]. Goran Cirovic, Simo Sudjic: Risk assessment in construction industry: The College of Civil Engineering and Geodesy
- [21]. Sachin Chauhan, Dr. Nihal Anwar Siddiqui: Hazards identification & risk assessment in construction industry: IJCRT: Volume 6, Issue 1 March 2018.
- [22]. Thabit H. Thabit, Saif Q. Younus: Risk Assessment and Management in Construction Industries: ISSN: 2348-7860 (O): Vol. 5 No. 2: February 2018
- [23]. Shapoorji Pallonji Construction Company Data: URL: https://www.shapoorjipallonji.com/pdfs/SP_E_And_C_achieves_50_Million_safe_manhours.pdf
- [24]. Ehsan, N., Mirza, E., Alam, M., & Ishaque, A. (2010, July). Notice of Retraction: Risk management in construction industry. In 2010 3rd International Conference on Computer Science and Information Technology (Vol. 9, pp. 16-21). IEEE.
- [25]. Hinze, J., Pedersen, C., & Fredley, J. (1998). Identifying root causes of construction injuries. Journal of Construction Engineering and Management, 124(1), 67-71.
- [26]. Hughes, P. W., & Ferrett, E. (2005). Introduction to health and safety in construction. Oxford: Elsevier Butterworth-Heinemann.
- [27]. Roozbeh Kangari and Leland S. Riggs, 1989 "Construction Risk Assessment by Linguistics", IEEE Transactions on Engineering Management, 36, 2-8,
- [28]. He Zhi, 1995 "Risk management for overseas construction projects", International Journal of Project Management"13, 231-237.
- [29]. Robert J. Chapman 2001, "The controlling influences on effective risk identification and assessment for construction design management", International Journal of Project Management .19 .147-160.
- [30]. Shou Qing Wang, Mohammed Fadhil Dulaimi and Muhammad Yousuf Aguria, 2004 "Risk management framework for construction projects in developing countries" Construction Management and Economics. 22 237–252.
- [31]. Edmundas Kazimieras Zavadskas, Zenonas Turskis and Jolanta Tamošaitiene, 2010 "Risk assessment of construction projects", Journal of Civil Engineering and Management, 16.33–46.



Volume 2, Issue 2, June 2022

- [32]. A. Mohan, V.Saravana Karthika, J. Ajith, Lenin dhal, M. Tholkapiyan, "Investigation on ultra-high strength slurry infiltrated multiscale fibre reinforced concrete", Materials Today : Proceedings, ISSN: 1904-4720, Volume 22, 904-911, 2020.
- [33]. V.Saravana Karthika, A.Mohan, R.Dinesh Kumar, Chippymol James, "Sustainable Consideration By Characterization Of Concrete Through Partial Replacement Of Fine Aggregate Using Granite Powder And Iron Powder", Journal of Green Engineering. ISSN: 1904-4720 (Print) 2245-4586 (Online) Volume 9, Issue 4, 514-525, December 2019.
- [34]. M. Jothilakshmi, L. Chandrakanthamma, K. S. Dhaya Chandhran, A. Mohan, "Flood control and water management at basin level at Orathur of kanchipuram district", International Journal of Engineering and Advanced Technology, ISSN: 2249-8958, Volume8, Issue 6S3, 1418-1421.September 2019.
- [35]. R. Gopalakrishnan, VM Sounthararajan, A. Mohan, M. Tholkapiyan, "The strength and durability of flyash and quarry dust light weight foam concrete", Materials Today: Proceedings, ISSN: 1904-4720, Volume 22, 1117-1124, 2020.
- [36]. K. S. Dhaya Chandhran, M. Jothilakshmi, L. Chandhrkanthamma, A. Mohan, "Thermal Insulation and R-Value Analysis for wall Insulated with PCM", International Journal of Innovative Technology and Exploring Engineering, ISSN: 2278-3075, Volume8, Issue 11-16, October 2019.
- [37]. Srividhya K, Mohan A, Tholkapiyan M, Arunraj A, "Earth Quake Mitigation (EQDM) Through Engineering Design", Materials Today: Proceedings, ISSN:1904-4720, Volume 22, 1074-1077, 2020.
- [38]. Dhayachandhran K S, Jothilakshmi M, Tholkapiyan M, Mohan A, "Performance Evaluation and R-Value for Thermally Insulated Wall with Embedding Fluted Sheets", Materials Today: Proceedings, ISSN: 1904-4720, Volume 22, 912-919, 2020.
- [39]. Rasli .A Md , & Wan Maseri Wan Mohd. (2008). Project performance framework: "The role of knowledge management and information technology infrastructure". Asian Journal of Business and Accounting, 1(2), 39-64.
- [40]. The Victorian Government (2009) "Supplementary Guidance Project Risk Management Guideline" Version 1.0.
- [41]. Tillmann Sachs, S.M and Robert L. K. Tiong, (2009), "Quantifying Qualitative Information on Risks Development of the QQIR Method", Journal of Construction Engineering and Management.
- [42]. Uher T.E and Toakely A.R., "Risk management in conceptual phase of a project".1999.
- [43]. Wang S. Q. and Dulami M. F. (2000), Risk management frame work for construction projects in developing countries.
- [44]. Roozbeh Kangari and Leland S. Riggs, 1989 "Construction Risk Assessment by Linguistics", IEEE Transactions on Engineering Management, 36, 2-8,
- [45]. He Zhi, 1995 "Risk management for overseas construction projects", International Journal of Project Management"13, 231-237.
- [46]. Robert J. Chapman 2001, "The controlling influences on effective risk identification and assessment for construction design management", International Journal of Project Management .19 .147-160.
- [47]. Shou Qing Wang, Mohammed Fadhil Dulaimi and Muhammad Yousuf Aguria, 2004 "Risk management framework for construction projects in developing countries" Construction Management and Economics. 22 237–252.
- [48]. Edmundas Kazimieras Zawada's, ZenonasTurskis and Jolanta Tamosaitiene, 2010 "Risk assessment of construction projects", Journal of Civil Engineering and Management, 16.33–46.
- [49]. A. Mohan, V.Saravana Karthika, J. Ajith, Lenin dhal, M. Tholkapiyan, "Investigation on ultra-high strength slurry infiltrated multiscale fibre reinforced concrete", Materials Today : Proceedings, ISSN: 1904-4720, Volume 22, 904-911, 2020.
- [50]. V.Saravana Karthika, A.Mohan, R.Dinesh Kumar, Chippymol James, "Sustainable Consideration By Characterization of Concrete Through Partial Replacement Of Fine Aggregate Using Granite Powder And Iron Powder", Journal of Green Engineering. ISSN: 1904-4720 (Print) 2245-4586 (Online) Volume 9, Issue 4, 514-525, December 2019.