

# Development of an IoT-Based Smart Street Lighting and Solar Generation Monitoring System for Energy Conservation

Arvind Verma, Hari Om, Harshit Gupta, Mayank Mudgal, Dr. Rakesh Kumar Joon, Mr. Satish  
Ganga Institute of Technology & Management, Kablana

**Abstract:** *Municipal street lighting represents a critical public infrastructure service that accounts for roughly 18% to 38% of total global energy expenditures within public spaces. Conventional High-Intensity Discharge (HID) luminaires operate continuously at peak capacity irrespective of real-time pedestrian or vehicular traffic, resulting in significant electrical waste, inflated utility costs, and heightened carbon footprints. This paper presents the architecture, implementation, and empirical verification of an affordable, automated, and Internet of Things (IoT)-enabled Energy Conservation System. The system replaces obsolete HID fixtures with directional, dimmable Light Emitting Diodes (LEDs) controlled by an ESP8266 NodeMCU microcontroller framework. Utilizing an array of Light Dependent Resistors (LDRs) and active Infrared (IR) sensors, the localized firmware alters luminaire illumination levels dynamic to environmental lighting changes and live object presence. Concurrently, the system acts as a micro-generation hub, incorporating a photovoltaic solar panel integrated with a telemetry network that reports real-time voltage generation data to the cloud using HTTP web protocols. Experimental outcomes demonstrate substantial power consumption savings, simplified maintenance telemetry, and reduced light pollution, paving a realistic pathway toward sustainable smart-city frameworks.*

**Keywords:** Energy Conservation, Smart Street Light, Internet of Things (IoT), ESP8266 NodeMCU, Infrared Sensor, Photo-Conductivity, Cloud Data Analytics

## I. INTRODUCTION

With accelerating global urbanization, demand for electrical power continues to outpace generation capacity, creating severe resource deficits, peak load vulnerabilities, and persistent brownouts. Municipal street lighting installations, though vital for civic safety and nocturnal transport, exacerbate this issue by drawing massive quantities of unoptimized grid power [1-3]. Traditional lighting controls rely heavily on manual operation or rigid mechanical timers that fail to adapt to ambient cloud cover, varying seasonal day-lengths, or low-footfall intervals [4].

To overcome these structural deficits, advanced automation solutions leveraging the Internet of Things (IoT) have been proposed. IoT infrastructures enable the fusion of sensory observation with distributed computing architectures, enabling edge components to capture environmental metrics and orchestrate context-aware control [5].

This research paper outlines a dual-purpose embedded energy conservation model. The primary subsystem replaces power-intensive HID bulbs with dimmable, directional LEDs regulated by a combination of LDR and IR sensor loops to dynamically scale brightness based on live object proximity [6]. The secondary subsystem incorporates localized solar generation tracking to monitor renewable offsets, streaming micro-generation statistics to an open-access cloud platform. This configuration provides municipal authorities with real-time grid diagnostics and consumption metrics while ensuring significant base-load electrical conservation [7-8].



## **II. LITERATURE REVIEW**

### **2.1 Evolution of Smart Street Lighting Systems**

Traditional street lighting systems are inefficient due to continuous operation, lack of automation, and dependence on manual control. Recent studies highlight that street lighting can consume a significant portion of urban electricity budgets, making optimization essential [9-12].

Smart street lighting has emerged as a key component of smart cities, integrating sensors, controllers, and communication networks. These systems enable real-time monitoring, fault detection, and adaptive lighting control, significantly improving operational efficiency and reducing maintenance costs [13-15].

### **2.2 Role of IoT in Smart Lighting**

The integration of the Internet of Things (IoT) has transformed conventional lighting into intelligent systems capable of autonomous decision-making. IoT-enabled lighting systems utilize distributed sensors and cloud platforms to collect and process environmental data [16].

Research shows that IoT-based lighting infrastructures allow:

- Remote monitoring and control
- Real-time data analytics
- Automated response to environmental conditions

Such systems eliminate manual intervention and reduce energy waste by adapting lighting levels based on actual demand.

A comprehensive survey (2024) emphasizes that IoT facilitates **networked communication between lighting nodes**, enabling dynamic brightness adjustment and large-scale energy savings in urban environments.

## **III. SENSOR-BASED ADAPTIVE LIGHTING TECHNIQUES**

Modern smart lighting systems rely heavily on sensors such as:

- LDR (Light Dependent Resistor) for ambient light detection
- IR/PIR sensors for motion detection

These sensors enable **adaptive illumination**, where light intensity varies based on environmental conditions and human activity [17-20].

Studies demonstrate that adaptive systems significantly outperform static lighting systems by reducing unnecessary power consumption during low-traffic periods.

Additionally, IoT-based adaptive lighting systems incorporate wireless sensor networks that allow distributed intelligence and real-time responsiveness [21-22].

## **IV. ENERGY EFFICIENCY THROUGH LED TECHNOLOGY**

The transition from High-Intensity Discharge (HID) lamps to LED lighting is a major advancement in energy conservation. LEDs offer:

- Lower power consumption
- Longer lifespan
- Better directional lighting

Research consistently shows that combining LED technology with smart control systems results in **substantial energy savings and reduced carbon emissions**.

## **V. SOLAR INTEGRATION IN SMART STREET LIGHTING**

Solar-powered street lighting systems further enhance sustainability by reducing dependency on grid power. These systems typically include:

- Photovoltaic (PV) panels



- Battery storage systems
- Charge controllers

Recent research highlights that integrating solar generation with smart lighting systems allows **hybrid energy models**, where renewable energy offsets grid consumption.

However, challenges such as energy storage optimization, weather variability, and system cost remain areas of active research.

## **VI. CLOUD-BASED MONITORING AND DATA ANALYTICS**

Cloud platforms play a crucial role in IoT-based lighting systems by enabling:

- Centralized monitoring
- Data logging and visualization
- Predictive maintenance

Advanced systems transmit real-time data to cloud servers, allowing municipal authorities to analyze energy consumption patterns and detect faults remotely.

Emerging research also explores integration with AI and machine learning for predictive analytics and optimization of lighting performance.

## **VII. CHALLENGES AND RESEARCH GAPS**

Despite significant advancements, several limitations persist in current systems:

- **Sensor reliability issues** due to low-cost hardware
- **Scalability challenges** in large urban deployments
- **Incomplete utilization of collected data**
- **Cybersecurity concerns in IoT networks**

Recent studies emphasize that while IoT-based lighting systems are functionally mature, they still lack full integration of intelligent analytics and robust system design.

## **VIII. SYSTEM ARCHITECTURE AND HARDWARE CONFIGURATION**

The system relies on a central Processing and Wireless Communications Core paired with a specialized Sensory Network and Power Generation framework.

### **8.1 Central Processing and Telemetry Unit (ESP8266 NodeMCU)**

The core computing backbone is built around the ESP8266-12E NodeMCU platform, an integrated microcontroller featuring an L106 32-bit RISC microprocessor capable of running at clock speeds up to 160 MHz. The system contains 80 KiB of user-data RAM alongside a built-in IEEE 802.11 b/g/n Wi-Fi stack. The integrated Wi-Fi stack allows the board to operate as an independent station, establishing client-side HTTP linkages with remote cloud databases to log local parameters without requiring separate, external network adapters.

### **8.2 Sensory Acquisition Array**

**Optical Tracking Component (LDR):** Ambient illumination tracking relies on a semiconductor Light Dependent Resistor operating via photo-conductivity. When exposed to sunlight, electromagnetic radiation drops the internal resistance of the LDR, providing a direct analog scale of surrounding light conditions to distinguish day from night.

**Proximity Tracking Component (Active IR Module):** Pedestrian and vehicular movement tracking uses active Infrared (IR) transceiver modules. Each module combines an IR emitting LED and a highly sensitive reverse-biased photodiode receiver. When an object enters the detection field, the emitted infrared light reflects back onto the photodiode, triggering a sharp resistance drop that signals the NodeMCU to ramp up luminaire brightness.



**Environmental Atmospheric Monitoring:** A digital DHT11 sensor tracks ambient conditions, outputting calibrated, composite streams of local temperature and relative humidity data.

### 8.3 Micro-Generation and Telemetry Subsystem

The system acts as an independent renewable generation station using a localized photovoltaic (PV) solar panel. The panel captures solar photons to generate clean DC electricity. To safely monitor this power output without damaging the microcontroller's 10-bit analog-to-digital converter (ADC), a voltage division sensor network steps down the raw generation voltages to a safe scale ( $0-3.3\text{V}$ ), matching the input limits of the ESP8266 platform.

## IX. SYSTEM METHODOLOGY AND WORKING PRINCIPLE

The operational execution of the system alternates continuously between active power minimization routines and data logging cycles.

### 9.1 Adaptive Street Lighting Control Loop

The street lighting framework uses an integrated approach combining LDR data and IR motion tracking:

During daylight intervals, high ambient light keeps LDR resistance low, ensuring the light arrays stay off.

At dusk, the system enters a reactive state. If the IR sensors report an idle state (`sensorStatus == 1`), the system leaves the lighting arrays off or dim, saving significant amounts of idle energy.

When a vehicle or pedestrian triggers an IR sensor array, the digital pin switches state (`LOW`). The NodeMCU instantly engages the drive relays, bringing the corresponding LED array to full brightness. The system holds this active state for a fixed timeout window ( $2,500\text{ms}$ ) before returning to an idle state once motion clears.

### 9.2 Solar Energy Harvest and Analytics Logging

Concurrently, the micro-solar panel absorbs sunlight photons, prompting electrons to break free from atomic orbits within its silicon layer via the Photovoltaic Effect. This process generates a proportional direct current (DC) output voltage.

The system reads this generation voltage through the analog pin (`SA_0`). To calculate the true potential across the solar array, the system scales the raw analog bits back up using the voltage divider ratio:

$$V_{OUT} = \frac{\text{value} \times 5.0}{1024.0}$$

$$V_{IN} = \frac{V_{OUT}}{\frac{R_2}{R_1 + R_2}}$$

## X. FIRMWARE IMPLEMENTATION

The firmware was constructed using the Arduino IDE environment. Below is the core program loop used to manage physical inputs and upload data to the cloud:

Algorithm: Energy Conservation System Using ESP8266

Step 1: Start

Step 2: Initialize System

Initialize LCD display.

Turn ON LCD backlight.

Set pin modes:



IR sensor pin as INPUT  
LED pin as OUTPUT  
Voltage sensor (A0) as INPUT  
Connect to WiFi using SSID and password.  
Wait until WiFi connection is established.  
Step 3: Read Voltage  
Read analog value from voltage sensor (A0).  
Convert analog value to output voltage:  
 $V_{OUT} = (\text{value} \times 5.0) / 1024$   
Calculate input voltage using voltage divider formula:  
 $V_{IN} = V_{OUT} / (R2 / (R1 + R2))$   
Display voltage on LCD.  
Step 4: Detect Human Presence (IR Sensor)  
Read IR sensor status.  
**If motion is detected (sensor = 0):**  
Turn ON LED (Light ON).  
Display "LIGHT STATUS: ON" on LCD.  
Display voltage again.  
Wait for 2.5 seconds.  
**Else (no motion detected):**  
Turn OFF LED (Light OFF).  
Display "LIGHT STATUS: OFF" on LCD.  
Step 5: Periodic Data Upload  
Check current time using `millis()`.  
If elapsed time  $\geq 40$  seconds:  
Update previous time.  
Create URL with voltage data.  
Send HTTP GET request to server (ThingSpeak).  
Display:  
"SOLAR DATA"  
"UPLOADING" on LCD.  
Step 6: Delay  
Wait for 200 milliseconds.  
Step 7: Repeat Loop  
Go back to **Step 3** and repeat continuously.  
Step 8: End (Continuous System)  
The system runs indefinitely.

## XI. SYSTEM DEPLOYMENT AND RESULTS

### 11.1 Physical Assembly

A functional prototype was built using structural fiberboards to simulate a scaled grid network flanked by smart street structures. The system was powered using an isolated 220VAC power adapter. Communication channels were initialized by pairing the NodeMCU with a local network gateway using standard access credentials (SSID: `esp`).

### 11.2 Environmental & Economic Outcomes

The prototype successfully met all targeted performance metrics:



Structural Parameter	Observed Operational Output
Idle State Consumption	Diminished to minimal levels via automated node shutdown.
Response Latency	<200ms delay between motion detection and array activation.
Telemetry Integrity	Generation metrics synced cleanly with the cloud dashboard every 40ms

By replacing traditional continuous-on lighting configurations with this adaptive framework, the system provides several key real-world advantages:

**Reduced carbon footprints** and light pollution.

**Lower system operating temperatures**, helping extend the lifespan of physical grid assets.

**Improved public safety** through on-demand visibility enhancements while remaining a highly cost-effective solution.

## XII. CONCLUSION

This paper demonstrates a practical, low-cost, and robust IoT implementation for modern energy conservation challenges. Combining adaptive lighting controls with cloud-synced solar generation analytics creates an effective framework for cutting municipal energy waste. While initial component setup costs are higher than traditional legacy installations, the long-term energy savings and reduced maintenance overhead make it a highly viable architecture for smart city infrastructure. Future iterations can explore adding mesh networking nodes and predictive energy algorithms to further improve system performance.

## REFERENCES

- [1]. P. Sarathi et al., "Smart Street Lighting System Using IoT," IEEE Internet of Things Journal, 2018.
- [2]. A De Almeida et al., "Energy Savings Potential of LED Street Lighting Systems," Energy and Buildings, 2014.
- [3]. K. S. Sudhakar et al., "Intelligent Street Lighting System Using Sensors," IEEE Sensors Journal, 2016.
- [4]. A Zanella et al., "Internet of Things for Smart Cities," Future Generation Computer Systems, 2014.
- [5]. M. A. Hossain et al., "Solar Powered LED Street Lighting," Renewable Energy, 2017.
- [6]. M. Aazam et al., "Cloud-Based IoT Framework," IEEE Access, 2016.
- [7]. S. Shaikh et al., "Automatic Street Light Control Using IR Sensors," IJERT, 2019.
- [8]. S. E. Bibri and J. Krogstie, "Energy Optimization in Smart Cities," Applied Energy, 2017.
- [9]. A Omar, "Smart City: Recent Advances in Intelligent Street Lighting Systems Based on IoT," Journal of Sensors, 2022.
- [10]. M. Mahoor et al., "State-of-the-art in Smart Streetlight Systems: A Review," IET Smart Cities, 2020.
- [11]. "A Comprehensive Survey on IoT-Based Smart Public Street Lighting Systems," ScienceDirect, 2024.
- [12]. Supreetha D. et al., "IoT-Based Smart Adaptive Street Lighting System," IJRITCC, 2019.
- [13]. J. Lillaney et al., "Automated Smart Street Lighting Model with Cloud Deployment," IEEE Conference, 2023.
- [14]. M. Manyake et al., "IoT Framework for Smart Public Lighting Systems," IEEE Conference, 2022.
- [15]. M. Kathe et al., "IoT-enabled Smart Street Light Power Management Systems," 2024.
- [16]. "IoT-enabled Smart Street Lighting: Challenges and Gaps," Preprints, 2026.
- [17]. A Patil et al., "Automated Street Lighting Using PIR Sensor, Arduino, and LDR," Journal of Control and Instrumentation Engineering, 2024.
- [18]. S. Debata et al., "IoT Based Smart Street Light Intensity Control Using IR and LDR Sensors," International Journal of Engineering and Technology, 2018.
- [19]. D. Danang et al., "Design of Intelligent Street Lighting Systems Based on Motion and Ambient Light Sensors," J-MART, 2026.
- [20]. D. Danang et al., "Intelligent Lighting System Using PIR and LDR Sensors," Journal of Multidisciplinary Research and Technology, 2024.



- [21]. N. Venu et al., "IoT-Based Real-Time Street Light Control on Motion Detection," European Chemical Bulletin, 2023.
- [22]. A A. Shadli and D. Hanafi, "Intelligent Street Light Using Fuzzy Logic Control," Evolution in Electrical and Electronic Engineering, 2020.

